faytech, nice touch.

faytech TOUCH PC

	7“ Touch PC	8“ Touch PC	10“ Touch PC	12“ Touch PC	15“ Touch PC	17“ Touch PC	19“ Touch PC	22“ Touch PC
O/S	WinCE preinstalled; WinCE vorinstalliert	Linux preinstalled, including drivers for Windows operating systems; Linux vorinstalliert, inkl. Treiber für Windows Betriebsystem	Linux preinstalled, including drivers for Windows operating systems; Linux vorinstalliert, inkl. Treiber für Windows Betriebsystem	Linux preinstalled, including drivers for Windows operating systems; Linux vorinstalliert, inkl. Treiber für Windows Betriebsystem	Linux preinstalled, including drivers for Windows operating systems; Linux vorinstalliert, inkl. Treiber für Windows Betriebsystem	Linux preinstalled, including drivers for Windows operating systems; Linux vorinstalliert, inkl. Treiber für Windows Betriebsystem	Linux preinstalled, including drivers for Windows operating systems; Linux vorinstalliert, inkl. Treiber für Windows Betriebsystem	Linux preinstalled, including drivers for Windows operating systems; Linux vorinstalliert, inkl. Treiber für Windows Betriebsystem
CPU	SAMSUNG 400Mhz	Intel ATOM N270	Intel ATOM N270	Intel ATOM N270	Intel ATOM N270	Intel ATOM N270	Intel ATOM N270	Intel ATOM N270
Screen diagonal (Inch/cm): Bildschirmdiagonale (Inch /cm):	17,78	20	27	31,5	37,8	42,8	48	56
Display case (cm, WxHxD): Displaygehäuse (cm, BxHxT):	19.5 B x 13 H x 3.5 T	21.6X17.8X5	25.5X20X5	35.5x28x6	37.5X28.9X5.5	38.5X30.5X5.5	45.5X30.5X6	51X35X7
Display (cm, W x H): Display (cm, B x H):	15,5 B x 9,1 H	16.3X12.4	21X16	24.7x18.6	30.5X23	33.8X27	41.5X20.5	47.6X29.6
Mounting: Befestigung:	VESA-75 Befestigung VESA - 75 Mounting holes	VESA-100 Befestigung VESA-100 Mounting holes	VESA-100 Befestigung VESA-100 Mounting holes	VESA-100 Befestigung VESA-100 Mounting holes	VESA-100 Befestigung VESA-100 Mounting holes	VESA-100 Befestigung VESA-100 Mounting holes	VESA-100 Befestigung VESA-100 Mounting holes	VESA-100 Befestigung VESA-100 Mounting holes
Gross weight (inclusive cartonage, kg): Brutto-Gewicht (inkl. Verpackung, kg):	1,3	1,55	2,15	2,8	4,05	4,85	5,25	6,95
Net display weight (kg): Netto-Display-Gewicht (kg):	0,6	0,7	1,05	1,6	3,1	3,7	4,2	5,4
Aspect ratio: Seitenverhältnis:	16:9	4:3	4:3	4:3	4:3	4:3	16:10	16:10
Physical resolution: Physikalische Auflösung:	800x480	800X600	800x600	1024x768	1024x768	1280x1024	1440x900	1680x1050
Maximum showable resolution: Maximal darstellbare Auflösung:	1920x1200	1920x1200	1920x1200	1920x1200	1920x1200	1920x1200	1920x1200	1920x1200
Colours displayed: Anzahl darstellbare Farben:	262.144	262.144	262.144	262.144	16.200.000	16.200.000	16.200.000	16.200.000
Brightness (cd/m2): Helligkeit (cd/m2):	300	250	250	200	400 / 450	300	300	300
Contrast: Kontrast:	450:1	500：1	400：1	450:1	400:1	450: 1	500: 1	1000 ： 1
Typical reaction time Tr/Tf (ms): Typische Reaktionszeit Tr/Tf (ms):	10/15	10/15	25/50	35/40	5 / 20	5 / 11	2 / 6	1.3 / 3.7
Visual Angle horizontal, vertical (°): Betrachtungswinkel horizontal, vertikal (°):	150	70	120	160	65/60 ; 70 / 70	80/80; 80/80	60/70; 75/75	85/85; 85/89
Working power (V): Betriebsspannung (V)	11,5-13	11,5-13	11.5-13	11.5-13	11.5-13	11.5-13	11.5-13	11.5-13
Power consumption (W): Stromverbrauch (W):	6	7	12	12	24	20,4	25	36
Stand-By-Consumption (W): Stand-By-Verbrauch (W):	1	1	1	1	1	1	1	1
Operating temperature (°C): Betriebstemperatur (°C):	-20 to +60	0-60	0-60	0-60	0-60	0-60	0-60	0-60
Touch-panel: Touch-Panel:	4-wire resistiv	4-wire resistiv	4-wire resistiv	4-wire resistiv	4-wire resistiv	4-wire resistiv	4-wire resistiv	5-wire resistiv
Touch-connector: Touch-Anschluss:	USB	USB	USB	USB	USB	USB	USB	USB
Touch-panel-driver: Touch-Panel-Treiber:	Windows, Linux	Windows, Linux	Windows, Linux	Windows, Linux	Windows, Linux	Windows, Linux	Windows, Linux	Windows, Linux
Touch life (contacts): Lebensdauer Touch-Panel (Berührungen):	> 10 000 000	> 10 000 000	> 10 000 000	> 10 000 000	> 10 000 000	> 10 000 000	> 10 000 000	> 10 000 000
Response time touch-panel (ms): Reaktionszeit Touch-Panel (ms):	< 10	< 10	< 10	< 10	< 10	< 10	< 10	< 10
Surface hardness: Oberflächenhärtegrad:	3H	3H	3H	3H	3H	3H	3H	3H
Input force (g): Druckstärke (g):	20 ~ 150	20 ~ 150	20 ~ 150	20 ~ 150	20 ~ 150	20 ~ 150	20 ~ 150	20 ~ 150
Connectors, video: Anschlüsse, Bild:	N/A	1 x VGA Out, 1 x S - Video Out	1 x VGA Out, 1 x S - Video Out	1 x VGA Out, 1 x S - Video Out	1 x VGA Out, 1 x S - Video Out	1 x VGA Out, 1 x S - Video Out	1 x VGA Out, 1 x S - Video Out	1 x VGA Out, 1 x S - Video Out
Connectors. audio: Anschlüsse, Audio:	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out	1 x Mic - IN. 1 x Microphoneingang: 1 x Earphone Out, 1 x Kopfhörer Out
Additional connectors: Weitere Anschlüsse:	1 x Series Port, 1 x USB, 1 x Mini USB 1 x LAN	2 x Series Port, 4 x USB, 1 x LAN	2 x Series Port, 4 x USB, 1 x LAN	2 x Series Port, 4 x USB, 1 x LAN	2 x Series Port, 4 x USB, 1 x LAN	2 x Series Port, 4 x USB, 1 x LAN	2 x Series Port, 4 x USB, 1 x LAN	2 x Series Port, 4 x USB, 1 x LAN
Power-supply (included in delivery): Stromversorgung (im Lieferumfang):	230V, 12V, 2.5A	230V, 12V, 4A	230V, 12V, 8A	230V, 12V, 8A	230V, 12V, 8A	230V, 12V, 8A	230V, 12V, 8A	230V, 12V, 8A
Additional features: Weitere Eigenschaften:	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1G Flash; 128 MB RAM; 10/100 Mbit Ethernet; CF - Card	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1 x DDR2 RAM SOCKET; Mini PCI Express; 10/100/1000 Mbit Ethernet; CF - Card; S - ATA; 44 - Pin IDE; Space for 2.5" SSD + harddisk	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1 x DDR2 RAM SOCKET; Mini PCI Express; 10/100/1000 Mbit Ethernet; CF - Card; S - ATA; 44 - Pin IDE; Space for 2.5" SSD + harddisk	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1 x DDR2 RAM SOCKET; Mini PCI Express; 10/100/1000 Mbit Ethernet; CF - Card; S - ATA; 44 - Pin IDE; Space for 2.5" SSD + harddisk	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1 x DDR2 RAM SOCKET; Mini PCI Express; 10/100/1000 Mbit Ethernet; CF - Card; S - ATA; 44 - Pin IDE; Space for 2.5" SSD + harddisk	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1 x DDR2 RAM SOCKET; Mini PCI Express; 10/100/1000 Mbit Ethernet; CF - Card; S - ATA; 44 - Pin IDE; Space for 2.5" SSD + harddisk	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1 x DDR2 RAM SOCKET; Mini PCI Express; 10/100/1000 Mbit Ethernet; CF - Card; S - ATA; 44 - Pin IDE; Space for 2.5" SSD + harddisk	Loudspeaker/Lautsprecher; Touch-pen/Touchstift; 1 x DDR2 RAM SOCKET; Mini PCI Express; 10/100/1000 Mbit Ethernet; CF - Card; S - ATA; 44 - Pin IDE; Space for 2.5" SSD + harddisk
Optional functions Optionale Funktionen	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply ,GPS + GSM , Batterie/Battery	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply , RAM and SSD	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply , RAM and SSD	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply , RAM and SSD	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply , RAM and SSD	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply , RAM and SSD	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply , RAM and SSD	W- Lan, SAW- Touch- Panel; IP65 , ITPS , Bluetooth 2.0 , 6-36 V power supply , RAM and SSD