



TBI MOTION TECHNOLOGY CO., LTD.

No.91, Zhong Shan Rd., Tucheng Dist., New Taipei City 23680, Taiwan, R.O.C.

TEL:+886-2-22687211~4 FAX:+886-2-22687210

E-mail:tbi.tbi@msa.hinet.net http://www.tbimotion.com.tw







LINEAR

GUID

П

ALOG

2014/05-2000

Note : The appearance and specification may be changed without prior notice only if the requirement improves performance.

INEAR GUIDE





1986 TBI

Taiwan Ball Screw Industrial Co., Ltd. (*TBI*) was established in Tucheng Industrial District, Taipei, Taiwan. We were also the first manufacturer who produces ground type of precise ball screws in Taiwan.

91988

TBI established Research & Development Department and finished constructing the factory in Taichung that focuses on innovative products and producing precise grinding ball screws.

● 2002 Ссомтор

COMTOP was established and exported ball screws to world wide based on a professional and successful marketing sales system.

• 2010 (TR) <u>TBIMOTION</u>

(*TBI MOTION*) has integrated the technology of *TBI* and the marketing strategy of **COMTOP** to develop *TBI MOTION* in a leading place of Linear Motion Industry. The main products are Ball Screws, Linear Guides, Ball Splines, Single Axis Robot, Linear Ball Bearing, Couplings, and Ball Screw Accessaries... ...etc.



Linear Guideway

1.General Information

1-1	Advantage and Features of Linear Guide	1
1-2	The procedure of Selecting Linear Guide	4
1-3	Basic Load Rating and Service Life of Linear Guide	5
1-4	Working Load	13
1-5	Safety Factor and Load	19
1-6	Calculation of average working load	28
1-7	Calculation example	32
1-8	Installation of Linear Guide	42
1-9	Friction	54
1-10	Design of Rigidity	55
1-11	Accuracy	57
1-12 Lubrication		
1-13 Precautions of Linear Guide		

An INDEX

2. TBI MOTION Linear Guide

2-1	The Characteristics of TBI Linear Guide	61
2-2	TRH/TRS/TRC International standard linear guide	62
	The Structure of TR-series	63
	TR Model Number for Non-interchangable TR Type	65
	Model Number for Interchangable TR Type	66
	TRH-V Series Dimension Table	67
	TRH-F Series Dimension Table	69
	TRS-V Series Dimension Table	7
	TRS-F / TRC-V Series Dimension Table	73
	The Standard length and maxima length of linear rail / Type	75
	Accuracy Standard	7
	Determining the Magnitude of a Preload / Grease Nipples	79
	Mounting Location	
	Dust-proof / Linear Guide Self-lubrication Series Accessory	83
	Codes of accessories	
	Mounting-Surface Dimensional Tolerance	
2-3	TM Miniature Linear Guide	
	The suructure of TM-series / Accuracy / Preload	91
	Types of lubrication / Order Information / Model Number	
	TM-N Specification / TM-W Specification	
	TBI MOTION Linear Guideway Inquiry Form	97

1.General Introduction

1-1 Advantage and Features of Linear Guide

1-1-1 High Accuracy

Because linear guide has little friction resistance, only a small driving force is needed to move the load. Low frictional resistance helps the temperature rising effect be small. Thus, the frictional resistance is decreased and the accuracy could be maintained for long period than traditional slide system.

1-1-2 High Rigidity

The design of Linear Guide rail and block features an equal lead rating in all four directions that request sufficient rigidity load in all directions, and self-aligning capability to absorb installation-error. Moreover, a sufficient preload can be achieved to increase rigidity and makes it suitable for any kind of installation.

1-1-3 Easy for Maintenance

Compared with high-skill required scrapping process of traditional slide system, the Linear Guide can offer high precision even if the mounting surface is machined by milling or grinding. Moreover the interchangeability of Linear Guide gives a convenience for installation and future maintenance.

1-1-4 High Speed

Linear Guide block, rail and ball apply by contact point of Rolling system. Due to the characteristic of low frictional resistance, the required driving force is much lower than that in other systems, thus the power consumption is small. Moreover, the temperature rising effect is small even under high speed operation.

1-1-5 High Performance without Clearance(see Fig 1.1.1)

Drawing	Characteristics, Performance
	 Two trains of balls. In a Gothic-arch groove, each ball contacts the raceway at four points 45°-45°. It has constant contact point between ball and arc groove. Rigidity has high stability. Two-row design is able to perform an equal load rating in four directions.
	 Four trains of balls. The circular-arc groove has two contact points at 45°-45°(DF)-Four-Row Design features an equal load rating in all four directions with high rigidity. Four-row design is able to perform an equal load rating in four directions. Self-Aligning to absorb installation-error.
	 Four trains of balls. The circular-arc groove has two contact points at 45°-45° (DB). Four-Row Design features an equal load rating in all four directions with high rigidity. Low friction resistance promotes smooth operating condition.
	 Four trains of balls. In the Gothic-arch groove, each ball contacts the raceway at two points 45°-45°, Light preload, two contact points, Heavy preload, four contact points. It contrasts with traditional DB type, which has better rigidity at permissible Moment



The Contract table of four-row design with equal load rating and two-row Gothic design.



Table1.1.1 Four-Row Equal Load Ratting Design.

Table1.1.2 Two-Row Gothic Design.

As shown in the diagrams, each time the ball rolls, a slip occurs in an amount equal to the difference between the circumferences of the inner and outer surfaces of the ball in contact with the raceway (π d1) and (π d2). (This slip is called the differential slip). When the circumferential difference is too large, a slip occurs when the ball rolls. The friction coefficient between the ball and the raceway is several times greater when slip occurs than when there is no slip and frictional resistance increases substantially. Even under a preload or regular load, the ball and raceway contact one another at two points in the loading direction, as shown. Thus the difference between d1 and d2 can be small, as can the differential slip. This design gives rise to a smooth rolling motion.

1-2 The procedure of Select Linear Guide

1-2-1 Flowchart

		Set the conditions for the design of loadson the Linear Guide. •Space available for the guide part. •Frequency of use (duty cycle). •Dimensions (span, No. of blocks, No. of •Velocity (acceleration).
	1 Set the operating conditions	rails, and thrust). •Stroke length. •Installation direction (horizontal, vertical, •Required service life.
Span \ No. of blocks, and No. of rails changed	-	tilted, wall-hung, or suspended). •Service environment. •Magnitude of the applied load, direction, •Motion precision . and location.
Type or size changed	2 Select the correct type	 Select proper type, size and quantity (If applied with ballscrew, the size of guideway should be similar to diameter of ballscrew).
	3 Calculate the applied load	•Calculate the load that a Linear Guide block exerts on the Linear Guide.
	4 Calculate the equivalent load	 Convert the load that Linear Guide blocks exert in each direction into an equivalent load.
	5 Calculate the static safety factor	 Verify the value of the static safety factor for the basic static-load rating and Maximum applied load.
NO	Is the static safety factor verified?	2
	6 Calculate the mean load	 Average the applied loads which fluctuate during operation, and convert them into a mean load.
	7 Calculate the nominal life	•Calculate the running distance using the service-life equation.
	8 Calculate the service life in hours	 Using the service-life equation to calculate the running distance or hours
NO	Convert the running distance obtained into obtained satisfy the enquired Service life?) the service life in hours Does the value
	9 Forecast the rigidity	 Determine the redial clearance to be used. Determine the fastening methods to be used. Determine the rigidity at the fastened areas.
	10 Select the accuracy and precision	Determine the accuracy grade to be applied. Determine the mounting surface precision to be used. Select the precision level.
	11 Safety design	 Determine the lubricants (grease, oil, special lubrication, etc.) to be used. Determine the lubrication method (periodic greasing, forced lubrication, etc.) to be used.
	12 Completion of selection	 Determine the material (Standard, stainless steel, etc) to be used. Completion of selection. Determine the surface treatment (anticorrosion, appearance protection, etc) to be provided. Design contaminant protection (bellows, telescopic cover, etc.)

1-3 Basic Load Rating and Service Life of Linear Guide

When determining a model that would best suit your service conditions for a linear motion system, the load carrying capacity and service life of the model must be considered. To consider the load carrying capacity you should know the static safety factor of the model calculated based on the basic static load rating. Service life can be assessed by calculating the nominal life based on the basic dynamic load rating and checking to see if the values thus obtained meet your requirements.

The service life of a linear motion system refers to the total running distance that the linear motion system travels until flaking (the disintegration of a metal surface in scale-like pieces) occurs there to as a result of the rolling fatigue of the material caused by repeated stress on raceways and rolling elements.

Basic Load Rating : There are two basic load ratings for linear motion systems basic static load rating(Co), which sets the static permissible limits, and basic dynamic load rating (C).

1-3-1 Basic Static Load Rating (Co)

If a linear motion system, whether at rest or in motion, receives an excessive load or a large impact, a localized permanent set develops between the raceway and rolling elements. If the magnitude of the permanent set exceeds a certain limit, it hinders the smooth motion of the liner motion system.

The basic static load rating refers to a static load in a given direction with given magnitude such that the sum of the permanent set of the rolling elements and that of the raceway at the contact area under the most stress is 0.0001 times greater than the rolling element diameter. In linear motion systems, the basic static load rating is defined as the radial load. Thus the basic static load rating provides a limit on the static permissible load.

1-3-2 Basic Permissible Moment (Mx, My, Mz)

TBIMOTION

When a Linear Guide gets a force that makes the balls distorted to 1/10,000 of their diameter, we call the force as basic static permissible moment. Values of Mx, My, Mz are shown on Fig1.3.1, which suggest 3 axes of moment on a Linear Guide slide.



1-3-3 Static Safety Factor fs

A linear motion system may possibly receive an unpredictable external force due to vibration and impact while it is at rest or is moving or due to inertia resulting from start and stop. It is therefore necessary to consider the static safety factor against operating loads like these. The static safety factor (fs) indicates the ratio of a linear motion system load carrying capacity [basic static

load rating Co] to the load exerted there on.

 $fs = \frac{Co}{P} or \frac{Mo}{M}$

fs : static safety factor Co : basic static load rating (N) Mo : static permissible moment (N-mm) P : calculated load (N) M : calculated moment (N-mm)

To calculate a load exerted on the Linear Guide, the mean load necessary for calculating the service life and the maximum load necessary for calculating the static safety factor must be obtained in advance. In a system that is subjected to frequent starts and stops and is placed under machining loads, and one upon which a moment due to an overhang load is forcefully exerted, an excessive, load greater than expected may develop. When selecting the correct type of Linear Guide for your purpose, be sure that the type you are considering can bear the maximum possible load, both when stopped and when in operation. The table below specifies the standard values for the static safety factor.

Table1.3.1 Static Safety Factor fs

Machine used	Loading conditions	fs lower limit
Ordinary	Receives no vibration or impact	1.0-1.3
machine	Receives vibration and impact	2.0-3.0
Machina tool	Receives no vibration or impact	1.0-1.5
Machine tool	Receives vibration and impact	2.5-7.0

For large radial loads	$\frac{f_{h} \cdot f_{t} \cdot f_{c} C_{O}}{P_{R}} \ge fs$
For large reverse- radial loads	$\frac{f_{h} \cdot f_{t} \cdot f_{c} C_{OL}}{P_{L}} \ge fs$
For large lateral loads	$\frac{f_{h} \cdot f_{t} \cdot f_{c} C_{0T}}{P_{T}} \ge fs$

fs : Static safety factor		
Co : Basic static-load rating (radial)		(N)
CoL: Basic static-load rating (reverse-ra	dial)	(N)
Cot: Basic static-load rating (lateral)		(N)
PR : Calculated load (radial)		(N)
PL : Calculated load (reverse-radial)		(N)
PT : Calculated load (lateral)		(N)
fh : Hardness factor	(Fig1	.3.2)
ft : Temperature factor	(Fig1	.3.3)
fc : Contact factor	(Table1	.3.2)
	fs : Static safety factor Co : Basic static-load rating (radial) CoL: Basic static-load rating (reverse-ra Co⊤: Basic static-load rating (lateral) PR : Calculated load (radial) PL : Calculated load (reverse-radial) PT : Calculated load (lateral) fh : Hardness factor ft : Temperature factor fc : Contact factor	$\begin{array}{ll} fs: Static safety factor \\ Co: Basic static-load rating (radial) \\ CoL: Basic static-load rating (reverse-radial) \\ Cot: Basic static-load rating (lateral) \\ PR: Calculated load (radial) \\ PL: Calculated load (reverse-radial) \\ PT: Calculated load (lateral) \\ fh: Hardness factor \\ ft: Temperature factor \\ fc: Contact factor \end{array} $ (Fig1



1-3-4 (L)

Even when identical linear guideways in a group are manufactured in the same way or applied under the same condition, the service life may be varied. Thus, the service life is used as an indicator for determining the service life of a linear guideway system. The nominal life (L) is defined as the total running distance that 90% of identical linear guideways in a group, when they are applied under the same conditions, can work without developing laking.

1-3-5 Basic Dynamic Load Rating (C)

Basic dynamic load rating (C) can be used to calculate the service life when linear guideway system response to a load. The basic dynamic load rating (C) is defined as a load in a given direction and with a given magnitude that when a group of linear guideways operate under the same conditions. As the rolling element is ball, the nominal life of the linear guideway is 50 km. Moreover, as the rolling element is roller, the nominal life is 100 km.

1-3-6 Calculation of Nominal Life

The service lives of linear motion systems more or less vary from system to system even if they are manufactured to the same specifications and remain in service under the same operating conditions. Hence a guideline for determining the service life of a linear motion system is given based on nominal life, which is defined as follows. The nominal life refers to the total running distance that 90% of identical linear motion systems in a group, when interlocked with one another under the same conditions, can achieve without developing flaking. The nominal life(L) of a linear motion system can be obtained from the basic dynamic load rating (C) and load imposed (P) using the following equations.

For a linear motion system with balls

For a linear motion system with rollers $L = (\frac{f_h \cdot f_h}{f_h})$

$$L = \left(\frac{f_{h} \cdot f_{t} \cdot f_{c}}{f_{W}} \cdot \frac{C}{P_{c}} \right)^{3} \cdot 50$$
$$L = \left(\frac{f_{h} \cdot f_{t} \cdot f_{c}}{f_{W}} \cdot \frac{C}{P_{c}} \right)^{\frac{10}{3}} \cdot 100$$

Service-Life Equation

The service life of the Linear Guide can be obtained using the following equation :

$$L = \left(\begin{array}{c} \frac{f_{h} \cdot f_{t} \cdot f_{c}}{f_{W}} \cdot \frac{C}{P_{c}} \end{array} \right)^{3} \cdot 50$$

(total distance that can be traveled by at least 90% of a group of Linear Guide operated under the same conditions)

C: basic dynamic-load rating	(N)
Pc : calculated load	(N)
fh : hardness factor	(Fig1.3.2)
ft : temperature factor	(Fig1.3.3)
fc : contact factor	(Table1.3.3)
fw : load factor	(Table1.3.4)

(Once nominal life (L) is obtained using this equation. The Linear Guide service life can be calculated by using the following equation if the stroke length and the number of reciprocating cycles are constant :



- L_h : service life in hours (h)
- ℓ s : stroke length (mm)
- n1 : No. of reciprocating cycles per min (min⁻¹)

[fh : Hardness factor]

To ensure achievement of the optimum loadbearing capacity of the Linear Guide, the raceway hardness must be 58~64HRC. At a hardness below this range, the basic dynamic and Static-load ratings decrease.

The ratings must therefore be multiplied by the

respective hardness factors (fh). As the Linear Guide has sufficient hardness, fh for the Linear Guide is 1.0 unless otherwise specified.



[ft : Temperature factor]

For Linear Guide used at ambient temperatures over 100°c, a temperature factor corresponding to the ambient temperature, selected from the diagram below, must be taken into consideration. In addition, please note that selected Linear Guide itself must be a model with hightemperature specifications.



(Note:When used at ambient temperatures higher than 80°c, the seals, end plates, and ball cages used must be change to those with hightemperature specifications.

[fc : Contact factor]

When multiple Linear Guide blocks are used laid over one another, moments and mountingsurface precision will affect operation, making it difficult to achieve uniform load distribution. For Linear Guide blocks used laid over one another, multiply the basic load rating (C), (C0) by a contact factor selected from the table below.

Table 1.3.2

No. of blocks used	Contact factor (fc)
2	0.81
3	0.72
4	0.66
5	0.61
6 or more	0.6
In normal use	1

Note: When the non-uniform load distribution can be predicted, as in a large system, consider using a contact factor.

[fw: Load factor]

In general, machines in reciprocal motion are likely to cause vibration and impact during operation, and it is particularly difficult to determine the magnitude of vibration that develops during high-speed operation as well as that of impact during repeated starting and stopping in normal use. Therefore, where the effects of speed and vibration are estimated to be significant divide the basic dynamic-load rating (C) by a load factor selected from the table below.

Table 1.3.3 Load Factor (fw)

Vibration and impact	Velocity(V)	fw
Very Slight	Very Low V 0.25m/s	1~1.2
Slight	Low 0.25 < V 1m/s	1.2~1.5
Moderate	Medium 1 < V 2m/s	1.5~2
Strong	High V > 2m/s	2~3.5

Calculation Examples :

Application : Machine Center

Block model number : TRH30FE (Basic static load Co=88.329kN, Basic dynamic load C=47kN)

The calculated load Pc=2614N

The formula of calculating the life time by travel is

 $L = \left(\frac{f_{h} \cdot f_{t} \cdot f_{c}}{f_{w}} \cdot \frac{C}{P_{c}} \right)^{3} \cdot 50 \text{ km}$

Since using only 1 block in this application, we take fc=1 Supposed the speed is not very high between 0.25~1m/s, so we take fw=1.5 The temperature of working environment is under 100°C. The temperature factor fT=1 The hardness of raceway is 58~64 HRC, so the hardness fH=1

With all above data, the life time by travel of this application L = 86112km

To calculate the life time by using hours : We supposed the distance of travel Ls = 3000 mm

Times (Back and forth) per mins N1 = 4 (min⁻¹)

The life time by travel is 86112km. the distance of travel is 3m (3000mm), so each back and forth is 6m.

The total times of back and forth would be 86112 x 1000 / 6 = 14352044

The life time by using minutes is 14352044 / 4 = 3588011 mins = 59800 hours



1-3-7 Service-Life Equation Lh

The Service Life can be calculated by operating term and velocity Nominal Life.

$$L_{h} = (\frac{L \cdot 10^{3}}{V_{e} \cdot 60}) = \frac{(\frac{C}{P})^{3} \cdot 50 \cdot 10^{3}}{Ve \cdot 60} \cdot hr$$

Lh : Service Life in Hour Ve : Velocity(m/min)

L : Nominal life(km) C/P : Load Ratio

Calculating Life Time

Formula (A) calculating hour

- Ln : Lifetime (h)
- L: Nominal life (km)
- Ls : Distance of travel (mm)
- N1 : Times of travel per minute (min⁻¹)

١n	$L \cdot 10^{6}$	
Ln =	2 · Ls · N1 · 60	

- Formula (B) calculating year
- Ly : Lifetime (year)
- L: Nominal life (km)
- Ls : Distance of travel (mm)
- N1 : Times of travel per minute (min⁻¹)
- Mn : Minutes of running per day (hr/day)
- Hn : Hours of running per day (hr/day)
- Dn : Days of running per year (day/year)



Example 1 : There is a working station using linear guides with a nominal life of 45000 km, how

should we calculate its service life in hours.

Known :

- Ls : Distance of travel = 3000mm (mm)
- N1 : 4 times of travel per minute (min⁻¹)

$$Ln = \frac{L \cdot 10^{6}}{2 \cdot Ls \cdot N1 \cdot 60} = \frac{45000 \cdot 10^{6}}{2 \cdot 3000 \cdot 4 \cdot 60} = 31250 \text{ hr}$$

Example 2 : There is a working station using linear guides with a nominal life 7123.5 km, how should we calculate its service life in hours.

Known :

- Ls : Distance of travel = 4000mm (mm)
- N1 : 5 times of travel per minute (min⁻¹)
- Ms : Running 60 mins per hour (min/hr)
- Hs : Running 24 hours per day (hr/day)
- Ds : Running 360 days per year (day/year)

$$L_{y} = \frac{L : 10^{6}}{2 \cdot L_{s} \cdot N1 \cdot M \cdot H \cdot D} = \frac{71231.5 : 10^{6}}{2 \cdot 4000 \cdot 5 \cdot 60 \cdot 24 \cdot 360} = 3.435 \text{ year}$$



1-4 Working Load

1-4-1 Working Load

The load applied to the Linear Guide, varies with the external force exerted thereon, such as the location of the center of gravity of an object been moved, the location of the thrust developed, inertia due to acceleration and deceleration during starting and stopping, and the machining resistance. To select the correct type of Linear Guide, the magnitude of applied loads must be determined in consideration of the above conditions to calculate accurate applied load.

To obtain the magnitude of an applied load and the service life in hours, the operating conditions of the Linear Guide system must first be set.

(1)Mass : m (kg)

(2)Direction of the action load

(3)Location of the action point (e.g., center of gravity) : L2 L3 h1 (mm)

(4)Location of the thrust developed : L4h2 (mm)

(5)Linear Guide system arrangement : L0L1 (mm)

(6)Velocity diagram

Velocity : V (mm/s) Time constant : tn (s) Acceleration : an (mm/s²)

 $a_n = \left(\frac{V}{t_n} \right)$

Gravitational acceleration g=9.8 m/s²



Fig1.4.1

(7)Duty cycle (No: of reciprocating cycles per min) : N1 (min¹)
(8)Stroke length : L (mm)
(9)Mean velocity : Vm (mm/s)

(10)Required service life in hoUrs : Lh (h)



Calculating the Working Load

The load applied to the Linear Guide varies with the external force exerted thereon, such as the location of the center of gravity of an object being moved, the location of the thrust developed, inertia due to acceleration and deceleration during starting and stopping, and the machining resistance. To select the correct type of Linear Guide, the magnitude of applied loads must be determined in consideration of the above conditions. Using the following Table1.4.1, we will now calculate the loads applied to the Linear Guide.

m : Mass	(kg)	g : Gravitational acceleration (m/s ²)	(g=9.8m/s ²
Ln : Distance	(mm)	V : Velocity	(m/s)
Fn : External force	(N)	tn: Time constant	(s)
Pn : Applied load	(N)	an : Acceleration	(m/s ²)
(radial and reverse-radial directions)		an = $\left(\frac{V}{tn}\right)$	
PnT : Applied load	(mm)		

Table1.4.1

NO.	Opearating conditions	Equation for calculating applied load
1	Install in a horizontal position. (Move the block) Ameasure in uniform motion or at rest.	$F_{1} = \frac{mg}{4} + \frac{mg \cdot L_{2}}{2 \cdot L_{0}} - \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$ $F_{2} = \frac{mg}{4} - \frac{mg \cdot L_{2}}{2 \cdot L_{0}} - \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$ $F_{3} = \frac{mg}{4} - \frac{mg \cdot L_{2}}{2 \cdot L_{0}} + \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$ $F_{4} = \frac{mg}{4} + \frac{mg \cdot L_{2}}{2 \cdot L_{0}} + \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$
2	Install in an overhung horizontal positon. (Move the block) Measure in uniform motion or at rest. F_{F_4} F_6 F_6 F_6 F_6 F_6 F_6 F_6 F_6 F_6 F_6 F_6 F_6 F_6 F_6	$F_{1} = \frac{mg}{4} + \frac{mg \cdot L_{2}}{2 \cdot L_{0}} + \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$ $F_{2} = \frac{mg}{4} - \frac{mg \cdot L_{2}}{2 \cdot L_{0}} + \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$ $F_{3} = \frac{mg}{4} - \frac{mg \cdot L_{2}}{2 \cdot L_{0}} - \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$ $F_{4} = \frac{mg}{4} + \frac{mg \cdot L_{2}}{2 \cdot L_{0}} - \frac{mg \cdot L_{3}}{2 \cdot L_{1}}$





NO.	Opearating conditions	Equation for calculating applied load
	Install in a longitudinally tilted position.	$F_{1} = + \frac{mg \cdot \cos \theta}{4} + \frac{mg \cdot \cos \theta \cdot L_{2}}{2 \cdot L_{0}}$ $- \frac{mg \cdot \cos \theta \cdot L_{3}}{2 \cdot L_{1}} + \frac{mg \cdot \sin \theta \cdot h_{1}}{2 \cdot L_{0}}$ $F_{1T} = + \frac{mg \cdot \sin \theta \cdot L_{3}}{2 \cdot L_{0}}$
7	Fai mg Fai Fai Fai Fai Fai Fai Fai Fai Fai Fai	$F_{2} = + \frac{mg \cdot \cos \theta}{4} - \frac{mg \cdot \cos \theta \cdot L_{2}}{2 \cdot L_{0}}$ $- \frac{mg \cdot \sin \theta \cdot L_{3}}{2 \cdot L_{1}} - \frac{mg \cdot \sin \theta \cdot h_{1}}{2 \cdot L_{0}}$ $F_{2T} = - \frac{mg \cdot \sin \theta \cdot L_{3}}{2 \cdot L_{0}}$ $F_{3} = + \frac{mg \cdot \cos \theta}{4} - \frac{mg \cdot \cos \theta \cdot L_{2}}{mg \cdot \cos \theta \cdot L_{2}}$
	La	$+\frac{\operatorname{mg}\cdot\cos\theta\cdot\mathrm{L}_{3}}{2\cdot\mathrm{L}_{1}}-\frac{\operatorname{mg}\cdot\sin\theta\cdot\mathrm{L}_{1}}{2\cdot\mathrm{L}_{0}}$ $F_{3T}=-\frac{\operatorname{mg}\cdot\sin\theta\cdot\mathrm{L}_{3}}{2\cdot\mathrm{L}_{0}}$ $F_{4}=+\frac{\operatorname{mg}\cdot\cos\theta}{2}+\frac{\operatorname{mg}\cdot\cos\theta\cdot\mathrm{L}_{2}}{2\cdot\mathrm{L}_{0}}$
	(EX) NC lathe / Tool res (for the lathe).	$+\frac{\operatorname{mg} \cdot \cos \theta \cdot L_{3}}{2 \cdot L_{1}} + \frac{\operatorname{mg} \cdot \sin \theta \cdot h_{1}}{2 \cdot L_{0}}$ $F_{4T} = +\frac{\operatorname{mg} \cdot \sin \theta \cdot L_{3}}{2 \cdot L_{0}}$
	Install in a horizontal position subjected mg to inertia.	During acceleration $F_1 = F_4 = \frac{mg}{4} - \frac{mg \cdot a_1 \cdot L_2}{2 \cdot L_0 \cdot g}$
		$F_{2} = F_{3} = \frac{mg}{4} + \frac{mg \cdot a_{1} \cdot L_{2}}{2 \cdot L_{0} \cdot g}$ $F_{1T} = F_{2T} = F_{3T} = F_{4T} = \frac{mg \cdot a_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g}$
8		$F_1 = F_2 = F_3 = F_4 = \frac{mg}{4}$
	$ \begin{array}{c} \widehat{\psi} \\ \widehat$	During deceleration $F_1 = F_4 = \frac{mg}{4} - \frac{mg \cdot a_3 \cdot L_2}{2}$
	² ¹ / ₁₀ (EX) vvagon Truck.	$F_{2} = F_{3} = \frac{mg}{4} + \frac{mg \cdot a_{3} \cdot L_{2}}{2 \cdot L_{0} \cdot g}$
	t1 t2 t3 Time(S)	$F_{1T} = F_{2T} = F_{3T} = F_{4T} = \frac{mg \cdot a_3 \cdot L_3}{2 \cdot L_0 \cdot g}$



LINEAR GUIDE



1-5 Safety Factor and Load

1-5-1 Equivalent Factors of Linear Guide Block

Where a sufficient installation space is not available you may be obliged to use just one Linear Guide block or two Linear Guide blocks laid over one another for the Linear Guide. In such a setting, the load distribution cannot be uniform and, as a result, an excessive load is exerted in localized areas (e.g., rail ends). Continued use under such conditions may result in flaking in those areas, consequently shortening the service life. In such a case, calculate true load by multiplying the moment value by any one of the moment-equivalent factors specified in Tables.



Fig.1.5.1 Ball Load Effected by a Moment

An equivalent-load equation applicable when a moment acts on a Linear Guides is shown below.

P=K.M

- P: equivalent load per Linear Guide (kgf)
- K : equivalent moment factor (mm⁻¹)
- M : developed moment (kgf · mm)

 $K_A^{\ }K_B^{\ }K_C$ represent the equivalent moment factors in directions $M_{A^{\ }}M_B$ and M_C respectively.

Calculation Examples

Two Linear Guide blocks are used laid over one another.

Model No : TRH30FE

Gravitational Acceleration g = 9.8m/s

Mass w = 5kgf

 $MC = 5 \cdot 150 = 750$ (kgf-mm)

 $MA = 5 \cdot 200 = 1000 \text{ (kgf-mm)}$



Fig.1.5.2

$$P_{1}=K_{c} \cdot \frac{M_{c}}{2} + K_{A} \cdot M_{A} + \frac{W}{2} = 7.15 \cdot 10^{2} \cdot \frac{750}{2} + 1.3 \cdot 10^{2} \cdot 1000 + \frac{5}{2} = 42.3 (kgf)$$

$$P_{2}=-K_{c} \cdot \frac{M_{c}}{2} + K_{A} \cdot M_{A} + \frac{W}{2} = -7.15 \cdot 10^{2} \cdot \frac{750}{2} + 1.3 \cdot 10^{2} \cdot 1000 + \frac{5}{2} = -11.3 (kgf)$$

$$P_{3}=K_{c} \cdot \frac{M_{c}}{2} - K_{A} \cdot M_{A} + \frac{W}{2} = 7.15 \cdot 10^{2} \cdot \frac{750}{2} - 1.3 \cdot 10^{2} \cdot 1000 + \frac{5}{2} = 16.3 (kgf)$$

$$P_{4}=-K_{c} \cdot \frac{M_{c}}{2} - K_{A} \cdot M_{A} + \frac{W}{2} = -7.15 \cdot 10^{2} \cdot \frac{750}{2} - 1.3 \cdot 10 \cdot \frac{1000}{1000} + \frac{5}{2} = -37.3 (kgf)$$

Note:

1. Since a Linear Guide in a vertical position receives only a moment load, there is no need to apply other loads (w).

2.In some models, load ratings differ depending on the direction of the applied load. With such a

model, calculate an equivalent load in a direction in which conditions are comparably bad.



Table1.5.1 TRH-F

	Equivalent F	actors Ka (mm ⁻¹)	Equivalent Factors Kb (mm ⁻¹)		Equivalent
Model No.	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Factors Kc (mm ⁻¹)
TRH15FN	1.48 x 10 ⁻¹	3.11 x 10 ⁻²	1.48 x 10 ⁻¹	3.11 x 10 ⁻²	1.34 x 10 ⁻¹
TRH15FL	1.26 x 10 ⁻¹	2.70 x 10 ⁻²	1.26 x 10 ⁻¹	2.70 x 10 ⁻²	1.34 x 10 ⁻¹
TRH15FE	1.01 x 10 ⁻¹	2.19 x 10 ⁻²	1. 01 x 10 ⁻¹	2.19 x 10 ⁻²	1.34 x 10 ⁻¹
TRH20FN	1.11 x 10 ⁻¹	2.35 x 10 ⁻²	1. 11 x 10 ⁻¹	2.35 x 10 ⁻²	9.90 x 10 ⁻²
TRH20FL	1.05 x 10 ⁻¹	2.20 x 10 ⁻²	1. 05 x 10 ⁻¹	2.20 x 10 ⁻²	9.90 x 10 ⁻²
TRH20FE	8. 00 x 10 ⁻²	1. 78 x 10 ⁻²	8. 00 x 10 ⁻²	1.78 x 10 ⁻²	9.90 x 10 ⁻²
TRH25FN	1. 04 x 10 ⁻¹	2. 17 x 10 ⁻²	1. 04 x 10 ⁻¹	2.17 x 10 ⁻²	8.62 x 10 ⁻²
TRH25FL	8. 82 x 10 ⁻²	1. 89 x 10 ⁻²	8. 82 x 10 ⁻²	1.89 x 10 ⁻²	8.62 x 10 ⁻²
TRH25FE	7. 35 x 10 ⁻²	1. 60 x 10 ⁻²	7. 35 x 10 ⁻²	1.60 x 10 ⁻²	8.62 x 10 ⁻²
TRH30FL	7. 74 x 10 ⁻²	1. 64 x 10 ⁻²	7. 74 x 10 ⁻²	1.64 x 10 ⁻²	7.15 x 10 ⁻²
TRH30FE	6.12 x 10 ⁻²	1. 33 x 10 ⁻²	6.12 x 10 ⁻²	1.33 x 10 ⁻²	7.15 x 10 ⁻²
TRH35FL	6. 99 x 10 ⁻²	1. 42 x 10 ⁻²	6. 99 x 10 ⁻²	1.42 x 10 ⁻²	5.85 x 10 ⁻²
TRH35FE	5. 25 x 10 ⁻²	1.15 x 10 ⁻²	5. 25 x 10 ⁻²	1.15 x 10 ⁻²	5.85 x 10 ⁻²
TRH45FL	5. 80 x 10 ⁻²	1. 24 x 10 ⁻²	5. 80 x 10 ⁻²	1.24 x 10 ⁻²	4.38 x 10 ⁻²
TRH45FE	4. 59 x 10 ⁻²	1. 00 x 10 ⁻²	4. 59 x 10 ⁻²	1.00 x 10 ⁻²	4.38 x10 ⁻²
TRH55FL	5. 25 x 10 ⁻²	1. 07 x 10 ⁻²	5. 25 x 10 ⁻²	1.07 x 10 ⁻²	3.78 x 10 ⁻²
TRH55FE	4. 08 x 10 ⁻²	8. 69 x 10 ⁻³	4. 08 x 10 ⁻²	8.69 x 10 ⁻³	3.78 x 10 ⁻²
TRH65FL	4. 52 x 10 ⁻²	8. 76 x 10 ⁻³	4. 52 x 10 ⁻²	8.76 x 10 ⁻³	3.24 x 10 ⁻²
TRH65FE	3. 27 x 10 ⁻²	6. 77 x 10 ⁻³	3. 27 x 10 ⁻²	677 x 10 ⁻³	3.24 x 10 ⁻²

LINEAR GUIDE

Ka : Equivalent moment factor in the pitching direction.

Kb : Equivalent moment factor in the yawing direction.

Kc : Equivalent moment factor in the rolling direction.

Table1.5.2 TRH-V

Model No.	Equivalent F	actors Ka (mm ⁻¹)	¹) Equivalent Factors Kb (mm ⁻¹)		Equivalent
Model No.	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Factors Kc (mm ⁻¹)
TRH15VN	1.48 x 10 ⁻¹	3.11 x 10 ⁻²	1.48 x 10 ⁻¹	3.11 x 10 ⁻²	1.34 x 10 ⁻¹
TRH15VL	1.26 x 10 ⁻¹	2.70 x 10 ⁻²	1.26 x 10 ⁻¹	2.70 x 10 ⁻²	1.34 x 10 ⁻¹
TRH20VN	1.11 x 10 ⁻¹	2.35 x 10 ⁻²	1.11 x 10 ⁻¹	2.35 x 10 ⁻²	9.90 x 10 ⁻²
TRH20VL	1.05 x 10 ⁻¹	2.20 x 10 ⁻²	1.05 x 10 ⁻¹	2.20 x 10 ⁻²	9.90 x 10 ⁻²
TRH20VE	8.00 x 10 ⁻²	1.78 x 10 ⁻²	8.00 x 10 ⁻²	1.78 x 10 ⁻²	9.90 x 10 ⁻²
TRH25VN	1.04 x 10 ⁻¹	2.17 x 10 ⁻²	1.04 x 10 ⁻¹	2.17 x 10 ⁻²	8.62 x 10 ⁻²
TRH25VL	8.82 x 10 ⁻²	1.89 x 10 ⁻²	8.82 x 10 ⁻²	1.89 x 10 ⁻²	8.62 x 10 ⁻²
TRH25VE	7.35 x 10 ⁻²	1.60 x 10 ⁻²	7.35 x 10 ⁻²	1.60 x 10 ⁻²	8.62 x 10 ⁻²
TRH30VL	7.74 x 10 ⁻²	1.64 x 10 ⁻²	7.74 x 10 ⁻²	1.64 x 10 ⁻²	7.15 x 10 ⁻²
TRH30VE	6.12 x 10 ⁻²	1.33 x 10 ⁻²	6.12 x 10 ⁻²	1.33 x 10 ⁻²	7.15 x 10 ⁻²
TRH35VL	6.99 x 10 ⁻²	1.42 x 10 ⁻²	6.99 x 10 ⁻²	1.42 x 10 ⁻²	5.85 x 10 ⁻²
TRH35VE	5.25 x 10 ⁻²	1.15 x 10 ⁻²	5.25 x 10 ⁻²	1.15 x 10 ⁻²	5.85 x 10 ⁻²
TRH45VL	5.80 x 10 ⁻²	1.24 x 10 ⁻²	5.80 x 10 ⁻²	1.24 x 10 ⁻²	4.38 x 10 ⁻²
TRH45VE	4.59 x 10 ⁻²	1.00 x 10 ⁻²	4.59 x 10 ⁻²	1.00 x 10 ⁻²	4.38 x 10 ⁻²
TRH55VL	5.25 x 10 ⁻²	1.07 x 10 ⁻²	5.25 x 10 ⁻²	1.07 x 10 ⁻²	3.78 x 10 ⁻²
TRH55VE	4.08 x 10 ⁻²	8.69 x 10 ⁻³	4.08 x 10 ⁻²	8.69 x 10 ⁻³	3.78 x 10 ⁻²
TRH65VL	4.52 x 10 ⁻²	8.76 x 10 ⁻³	4.52 x 10 ⁻²	8.76 x 10 ⁻³	3.24 x 10 ⁻²
TRH65VE	3.27 x 10 ⁻²	6.77 x 10 ⁻³	3.27 x 10 ⁻²	6.77 x 10 ⁻³	3.24 x 10 ⁻²

Ka : Equivalent moment factor in the pitching direction.

Kb : Equivalent moment factor in the yawing direction.

Kc : Equivalent moment factor in the rolling direction.



Table1.5.3 TRS-F

	Equivalent F	Factors Ka (mm ⁻¹)	Equivalent F	Factors Kb (mm ⁻¹)	
Model No.	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Factors Kc (mm ⁻¹)
TRS15FS	2.29x10 ⁻¹	4.39x10 ⁻²	2.29x10 ⁻¹	4.39x10 ⁻²	1.34x10 ⁻¹
TRS15FN	1.48x10 ⁻¹	3.11x10 ⁻²	1.48x10 ⁻¹	3.11x10 ⁻²	1.34x10 ⁻¹
TRS20FS	2.00x10 ⁻¹	3.58x10 ⁻²	2.00x10 ⁻¹	3.58x10 ⁻²	9.90x10 ⁻²
TRS20FN	1.25x10 ⁻¹	2.60x10 ⁻²	1.25x10 ⁻¹	2.60x10 ⁻²	9.90x10 ⁻²
TRS25FS	1.60x10 ⁻¹	3.07x10 ⁻²	1.60x10 ⁻¹	3.07x10 ⁻²	8.62x10 ⁻²
TRS25FN	1.04x10 ⁻¹	2.17x10 ⁻²	1.04x10 ⁻¹	2.17x10 ⁻²	8.62x10 ⁻²
TRS30FS	1.47x10 ⁻¹	2.57x10 ⁻²	1.47x10 ⁻¹	2.57x10 ⁻²	7.15x10 ⁻²
TRS30FN	8.65x10 ⁻²	1.82x10 ⁻²	8.65x10 ⁻²	1.82x10 ⁻²	7.15x10 ⁻²
TRS35FS	1.26x10 ⁻¹	2.30x10 ⁻²	1.26x10 ⁻¹	2.30x10 ⁻²	5.85x10 ⁻²
TRS35FN	7.87x10 ⁻²	1.61x10 ⁻²	7.87x10 ⁻²	1.61x10 ⁻²	5.85x10 ⁻²
TRS45FN	6.89x10 ⁻²	1.39x10 ⁻²	6.89x10 ⁻²	1.39x10 ⁻²	4.38x10 ⁻²

Ka : Equivalent moment factor in the pitching direction.

Kb : Equivalent moment factor in the yawing direction.

Kc : Equivalent moment factor in the rolling direction.

Table1.5.4 TRS-V

	Equivalent F	Factors Ka (mm ⁻¹)	Equivalent F	Equivalent Factors Kb (mm ⁻¹)	
Model No.	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Factors Kc (mm ¹)
TRS15VS	2.29x10 ⁻¹	4.39x10 ⁻²	2.29x10 ⁻¹	4.39x10 ⁻²	1.34x10 ⁻¹
TRS15VN	1.48x10 ⁻¹	3.11x10 ⁻²	1.48x10 ⁻¹	3.11x10 ⁻²	1.34x10 ⁻¹
TRS15VL	1.26x10 ⁻¹	2.70x10 ⁻²	1.26x10 ⁻¹	2.70x10 ⁻²	1.34x10 ⁻¹
TRS15VE	1.01x10 ⁻¹	2.19x10 ⁻²	1.01x10 ⁻¹	2.19x10 ⁻²	1.34x10 ⁻¹
TRS20VS	2.00x10 ⁻¹	3.58x10 ⁻²	2.00x10 ⁻¹	3.58x10 ⁻²	9.90x10 ⁻²
TRS20VN	1.25x10 ⁻¹	2.60x10 ⁻²	1.25x10 ⁻¹	2.60x10 ⁻²	9.90x10 ⁻²
TRS25VS	1.60x10 ⁻¹	3.07x10 ⁻²	1.60x10 ⁻¹	3.07x10 ⁻²	8.62x10 ⁻²
TRS25VN	1.04x10 ⁻¹	2.17x10 ⁻²	1.04x10 ⁻¹	2.17x10 ⁻²	8.62x10 ⁻²
TRS30VS	1.47x10 ⁻¹	2.57x10 ⁻²	1.47x10 ⁻¹	2.57x10 ⁻²	7.15x10 ⁻²
TRS30VN	8.65x10 ⁻²	1.82x10 ⁻²	8.65x10 ⁻²	1.82x10 ⁻²	7.15x10 ⁻²
TRS30VL	7.74x10 ⁻²	1.64x10 ⁻²	7.74x10 ⁻²	1.64x10 ⁻²	7.15x10 ⁻²
TRS30VE	6.12x10 ⁻²	1.33x10 ⁻²	6.12x10 ⁻²	1.33x10 ⁻²	7.15x10 ⁻²
TRS35VS	1.26x10 ⁻¹	2.30x10 ⁻²	1.26x10 ⁻¹	2.30x10 ⁻²	5.85x10 ⁻²
TRS35VN	7.87x10 ⁻²	1.61x10 ⁻²	7.87x10 ⁻²	1.61x10 ⁻²	5.85x10 ⁻²
TRS35VL	6.99x10 ⁻²	1.42x10 ⁻²	6.99x10 ⁻²	1.42x10 ⁻²	5.85x10 ⁻²
TRS35VE	5.25x10 ⁻²	1.15x10 ⁻²	5.25x10 ⁻²	1.15x10 ⁻²	5.85x10 ⁻²
TRS45VN	6.89x10 ⁻²	1.39x10 ⁻²	6.89x10 ⁻²	1.39x10 ⁻²	4.38x10 ⁻²
TRS45VL	5.80x10 ⁻²	1.24x10 ⁻²	5.80x10 ⁻²	1.24x10 ⁻²	4.38x10 ⁻²
TRS45VE	4.59x10 ⁻²	1.00x10 ⁻²	4.59x10 ⁻²	1.00x10 ⁻²	4.38x10 ⁻²

 $\mathsf{K} \mathsf{a}$: Equivalent moment factor in the pitching direction.

Kb : Equivalent moment factor in the yawing direction.

 $\mathsf{K}_{c}:$ Equivalent moment factor in the rolling direction.

Table1.5.5 TRC-V

	Equivalent F	actors Ka (mm ¹)	Equivalent F	Factors Kb (mm ¹)	
Model No.	Equivalent Load Calculationfor a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Factors Kc (mm ¹)
TRC25VL	8.82x10 ⁻²	1.89x10 ⁻²	8.82 x 10 ⁻²	1.89x10 ⁻²	8.62 x 10 ⁻²
TRC25VE	7.35x10 ⁻²	1.60×10 ⁻²	7.35 x 10 ⁻²	1.60x10 ⁻²	8.62 x 10 ⁻²

Ka : Equivalent moment factor in the pitching direction.

Kb : Equivalent moment factor in the yawing direction.

Kc : Equivalent moment factor in the rolling direction.

Table1.5.6 TM-N

	Equivalent F	actors Ka (mm ¹)	Equivalent F	actors Kb (mm ¹)	
Model No.	Equivalent Load Calculationfor a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Factors Kc (mm ¹)
TM07NN	8.88x10 ⁻¹	6.31x10 ⁻²	8.88x10 ⁻¹	6.31x10 ⁻²	2.74x10 ⁻¹
TM07NL	4.41x10 ⁻¹	5.16x10 ⁻²	4.41x10 ⁻¹	5.16x10 ⁻²	2.74x10 ⁻¹
TM09NN	4.41x10 ⁻¹	5.26x10 ⁻²	4.41x10 ⁻¹	5.26x10 ⁻²	2.19x10 ⁻¹
TM09NL	2.76x10 ⁻¹	4.08x10 ⁻²	2.76x10 ⁻¹	4.08x10 ⁻²	2.19x10 ⁻¹
TM12NN	4.90x10 ⁻¹	4.32x10 ⁻²	4.90x10 ⁻¹	4.32x10 ⁻²	1.64x10 ⁻¹
TM12NL	2.67x10 ⁻¹	3.42x10 ⁻²	2.67x10 ⁻¹	3.42x10 ⁻²	1.64x10 ⁻¹
TM15NN	3.60x10 ⁻¹	3.61x10 ⁻²	3.60x10 ⁻¹	3.61x10 ⁻²	1.32 x 10 ⁻¹
TM15NL	1.94x10 ⁻¹	2.76x10 ⁻²	1.94 x 10 ⁻¹	2.76x10 ⁻²	1.32 x 10 ⁻¹

 $\mathsf{Ka}:\mathsf{Equivalent}$ moment factor in the pitching direction.

Kb : Equivalent moment factor in the yawing direction.

Kc : Equivalent moment factor in the rolling direction.

	Equivalent F	Equivalent Factors Ka (mm ¹)		Equivalent Factors Kb (mm ¹)	
Model No.	Equivalent Load Calculationfor a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Load Calculation for a system Using One Linear Guide Block	Equivalent Load Calculation for a system Using Two Linear Guide Blocks laid Over One-Another	Equivalent Factors Kc (mm ¹)
TM09WN	2.27x10 ⁻¹	3.01x10 ⁻²	2.27x10 ⁻¹	3.01x10 ⁻²	7.92x10 ⁻²
TM09WL	1.30x10 ⁻¹	2.17x10 ⁻²	1.30x10 ⁻¹	2.17x10 ⁻²	7.14x10 ⁻²
TM12WN	1.85x10 ⁻¹	2.28x10 ⁻²	1.85x10 ⁻¹	2.28x10 ⁻²	5.20x10 ⁻²
TM12WL	1.12x10 ⁻¹	1.72x10 ⁻²	1.12x10 ⁻¹	1.72x10 ⁻²	5.05x10 ⁻²
TM15WN	1.56x10 ⁻¹	2.01x10 ⁻²	1.56x10 ⁻¹	2.01x10 ⁻²	3.24x10 ⁻²
TM15WL	9.07x10 ⁻²	1.47x10 ⁻²	9.07x10 ⁻²	1.47x10 ⁻²	3.07x10 ⁻²

Ka : Equivalent moment factor in the pitching direction.

Kb : Equivalent moment factor in the yawing direction.

Kc : Equivalent moment factor in the rolling direction.

1-5-2 Calculating the Equivalent Load

The Linear Guide can bear loads and moments in four directions, including a radial load (PR), reverse-radial load (PL), and lateral load (PT), simultaneously.

- PR : Radial load
- PL : Reverse-radial load
- P⊤: Lateral load
- MA : Moment in the pitching direction
- MB : Moment in the yawing direction
- Mc : Moment in the rolling direction



Fig1.5.4 Directions of the Load and Moment Exerted on the Linear Guide

Equivalent load PE

When more than one load (e.g., radial and lateral loads) is exerted on the Linear Guide simultaneously, the service life and static safety factors should be calculated using equivalent load values obtained by converting all loads involved into radial, lateral, and other loads involved.

Equivalent-load equation

The equivalent-load equations for the Linear Guide differ by guide type. For details, see the relevant sections.







Fig1.5.5 Linear Guide Equivalent load

The equivalent load when a radial load (PR) and a lateral load (PT) are applied simultaneously can be obtained using the following equation.

 $\label{eq:PE} \begin{array}{l} \mathsf{PE} \ : \ (\text{equivalent load}) = \mathsf{X} \ \cdot \ \mathsf{P}_{\mathsf{R}(\mathsf{L})} + \mathsf{Y} \ \cdot \ \mathsf{P}_{\mathsf{T}} \\ \\ \mathsf{PR} \ : \ \mathsf{Radial load} \end{array}$

PT : Lateral load



1-6 Calculation of average working load

1-6-1 Calculating the Mean Load

An industrial robot grasps a workpiece using its arm as it advances, moving further under the load. When it returns, the arm has no load other than its tare. In a machine tool, Linear Guide blocks receive varying loads depending on the host-system operating conditions.

The service life of the Linear Guides; therefore, should be calculated in consideration of such fluctuations in load.

The mean load (Pm) is the load under which the service life of the Linear Guide becomes equivalent to that under the varying loads exerted on the Linear Guide blocks

(1) For loads that change stepwise



Fig1.6.1

$P_{m} = \sqrt[3]{\frac{1}{L}} \cdot \Sigma \left(P_{n}^{3} \cdot L_{n} \right)$

Pm : mean load	(N)
Pn : varying load	(N)
Lc: total running distance	(mm)
Ln : running distance under load Pn	(mm)
Note : This equation and equation (1)	
below apply in cases in which t	he
rolling elements are balls.	
Pm : mean load	(N)
Pn: varying load	(N)
Lc: total running distance	(mm)
Ln: running distance under load Pn	(mm)











1-6-2 Mean Load Calculation Example ()

(1)Horizontal Installations Subjected to Acceleration and Deceleration



(2)Load applied to the Linear Guide block

.In uniform motion	2. During acceleration	3. During deceleration	
$P_1 = + \frac{mg}{d}$	$P_{a_1} = P_1 + \frac{m \cdot \alpha_1 \cdot L_2}{2 \cdot L_2}$	$P_{d_1} = P_{1} - \frac{m \cdot \alpha_1 \cdot L_2}{2 \cdot L_2}$	
$P_2 = + \frac{mg}{4}$	$P_{a_2} = P_2 + \frac{\mathbf{m} \cdot \alpha_1 \cdot \mathbf{L}_2}{2 \cdot \mathbf{L}_0}$	$P_{d_2} = P_2 + \frac{m \cdot \alpha_1 \cdot L_2}{2 \cdot L_0}$	
$P_3 = + \frac{mg}{4}$	$P_{a_3} = P_3 + \frac{m \cdot \alpha_1 \cdot L_2}{2 \cdot L_0}$	$P_{d_3} = P_3 + \frac{m \cdot \alpha_1 \cdot L_2}{2 \cdot L_0}$	
$P_4 = + \frac{mg}{4}$	$P_{a_4} = P_4 + \frac{m \cdot \alpha_1 \cdot L_2}{2 \cdot L_0}$	$P_{d_4} = P_4 + \frac{m \cdot \alpha_1 \cdot L_2}{2 \cdot L_0}$	

(3)Mean load

1

$$P_{m_{1}} = \sqrt[3]{\frac{1}{L_{s}} \left(P_{a_{1}^{3}} \cdot S_{1} + P_{1}^{3} \cdot S_{2} + P_{d}^{3} \cdot S_{3}\right)} P_{m_{3}} = \sqrt[3]{\frac{1}{L_{s}} \left(P_{a_{3}^{3}} \cdot S_{1} + P_{3}^{3} \cdot S_{2} + P_{d_{3}^{3}} \cdot S_{3}\right)} P_{m_{2}} = \sqrt[3]{\frac{1}{L_{s}} \left(P_{a_{2}^{3}} \cdot S_{1} + P_{2}^{3} \cdot S_{2} + P_{d_{2}^{3}} \cdot S_{3}\right)} P_{m_{4}} = \sqrt[3]{\frac{1}{L_{s}} \left(P_{a_{4}^{3}} \cdot S_{1} + P_{4}^{3} \cdot S_{2} + P_{d_{4}^{3}} \cdot S_{3}\right)}$$

Note: Pan, . Pdn represent loads exerted on the Linear Guide block. The suffix "n" indicates the block number in the diagram above.

2

L4 = 200 mm L5 = 400 mm

Mean Load Calculation Example ()

(1)Operating conditions-Installations on Rails.



(2)Load applied to the Linear G	Guide block	(3)Mean load
1.At the left of the arm	2.At the right of the arm	
$P_{L1} = + \frac{mg}{4} + \frac{mg \cdot L_1}{2 \cdot L_0}$	$P_{r_1} = + \frac{mg}{4} - \frac{mg \cdot L_1}{2 \cdot L_0}$	$P_{m_1} = \frac{1}{3} (2 \cdot P_{L_1} + P_{r_1})$
$P_{L2} = + \frac{mg}{4} - \frac{mg \cdot L_{1}}{2 \cdot L_{0}}$	$P_{r_2} = + \frac{mg}{4} + \frac{mg \cdot L_1}{2 \cdot L_0}$	$P_{m_1} = \frac{1}{3} (2 \cdot P_{L_2} + P_{r_2})$
$P_{L3} = + \frac{mg}{4} - \frac{mg \cdot L_{1}}{2 \cdot L_{0}}$	$P_{r_3} = + \frac{mg}{4} + \frac{mg \cdot L_1}{2 \cdot L_0}$	$P_{m_1} = \frac{1}{3} (2 \cdot P_{L_3} + P_{r_3})$
$P_{L4} = + \frac{mg}{4} + \frac{mg\cdotL_{1}}{2\cdotL_{0}}$	$P_{r4} = + \frac{mg}{4} - \frac{mg \cdot L_1}{2 \cdot L_0}$	$P_{m 1} = \frac{1}{3} (2 \cdot P_{L4} + P_{r4})$

Note: PLn . Pm represent loads exerted on the Linear Guide block. The suffix "n"

indicates the block number in the diagram above.

1-7 Calculation example

1-7-1 Calculation Examples

Example 1

(1)Operating conditions-Horizontal installations subjected to high acceleration and deceleration

	Velocity : V = 0.5 m/s	Acceleration : $\alpha 1 = 10 \text{ m/s}$
Model number : TRH30FE	Time : t1 = 0.05s	Acceleration : $\alpha 2 = 3.333 \text{ m/s}^2$
Basic dynamic-load rating C = 47kN	Time : t2 = 2.8s	Stroke:Ls = 1450 mm
Basic static-load rating C0 = 88.329kN	Time : $t_{3} = 0.15s$	Distance : $1.0 = 600 \text{ mm}$
Gravitational acceleration : $g = 9.8 (m/s^2)$		11 - 400 mm
Load : m1 = 6000N		$L_{1} = 400 \text{ mm}$
Load : m2 = 3800N		
		L3 = 50 mm







TBI

TBIMOTION



(2)Load Exerted on the Linear Guide by the Linear Guide Block

Calculate the load that each Linear Guide block exerts.

1.In uniform motion Load applied in radial direction Pn. (Base on the first condition of Load exerted [please see page14, No.1] , that's regarding influence of m1g and m2g.

$P_{A} = \frac{m1g}{4} - \frac{m1g \cdot L_{2}}{2 \cdot L_{0}} + \frac{m1g \cdot L_{3}}{2 \cdot L_{1}} + \frac{m2g}{4} = 2325 \text{ N}$	$P_{c} = \frac{m1g}{4} + \frac{m1g \cdot L_{2}}{2 \cdot L_{0}} - \frac{m1g \cdot L_{3}}{2 \cdot L_{1}} + \frac{m2g}{4} = 2575 \mathrm{N}$
$P_{B} = \frac{m1g}{4} + \frac{m1g \cdot L_{2}}{2 \cdot L_{0}} + \frac{m1g \cdot L_{3}}{2 \cdot L_{1}} + \frac{m2g}{4} = 3325 \text{ N}$	$P_{D} = \frac{m1g}{4} - \frac{m1g \cdot L_{2}}{2 \cdot L_{0}} - \frac{m1g \cdot L_{3}}{2 \cdot L_{1}} + \frac{m2g}{4} = 1575 \text{ N}$

2.During acceleration to the left Load applied in radial direction PnLa and lateral direction PntLa (Base on the 8th condition of load exerted [please see page 17. No.8] . The load should allocate on the central of table, and $\frac{m_1g}{4}$ should be re-placed by Pn).

$$P_{A}L_{a}=P_{A}-\frac{m1g\cdot\alpha_{1}\cdot L_{5}}{2\cdot L_{0}\cdot g}-\frac{m2g\cdot\alpha_{1}\cdot L_{4}}{2\cdot L_{0}\cdot g}=-362N$$

$$P_{0}L_{a}=P_{0}-\frac{m1g\cdot\alpha_{1}\cdot L_{5}}{2\cdot L_{0}\cdot g}-\frac{m2g\cdot\alpha_{1}\cdot L_{4}}{2\cdot L_{0}\cdot g}=5262.1N$$

$$P_{0}L_{a}=P_{0}-\frac{m1g\cdot\alpha_{1}\cdot L_{5}}{2\cdot L_{0}\cdot g}-\frac{m2g\cdot\alpha_{1}\cdot L_{4}}{2\cdot L_{0}\cdot g}=1112.1N$$

$$P_{At}L_{a} = -\frac{m1g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = -255.1 \text{ N}$$

$$P_{Ct}L_{a} = -\frac{m1g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = 255.1 \text{ N}$$

$$P_{Bt}L_{a} = -\frac{m1g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = 255.1 \text{ N}$$

$$P_{Dt}L_{a} = -\frac{m1g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = -255.1 \text{ N}$$

3. During deceleration to the left Load applied in radial direction PnLd

$$P_{A}L_{d} = P_{A} + \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot d_{0} \cdot g} + \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 3220.6 \text{ N} \qquad P_{c}L_{d} = P_{c} - \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot L_{0} \cdot g} - \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 1679.4 \text{ N}$$

$$P_{B}L_{d} = P_{B} - \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot L_{0} \cdot g} - \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 2429.4 \text{ N} \qquad P_{D}L_{d} = P_{D} + \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot L_{0} \cdot g} + \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 2470.6 \text{ N}$$

Load applied in lateral direction PntLd

$$P_{A_{1}}L_{d} = \frac{m1g \cdot \alpha_{3} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = 85 N$$

$$P_{C_{1}}L_{d} = -\frac{m1g \cdot \alpha_{3} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = -85 N$$

$$P_{D_{1}}L_{d} = -\frac{m1g \cdot \alpha_{3} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = 85 N$$

4. During acceleration to the right Load applied in radial direction PnRa

$$P_{A}R_{a}=P_{A}+\frac{m1g\cdot\alpha_{1}\cdot L_{5}}{2\cdot L_{0}\cdot g}+\frac{m2g\cdot\alpha_{1}\cdot L_{4}}{2\cdot L_{0}\cdot g}=4982.1 \text{ N} \quad P_{C}R_{a}=P_{C}-\frac{m1g\cdot\alpha_{1}\cdot L_{5}}{2\cdot L_{0}\cdot g}-\frac{m2g\cdot\alpha_{1}\cdot L_{4}}{2\cdot L_{0}\cdot g}=-112.1 \text{ N}$$

$$P_{B}R_{a}=P_{B}-\frac{m1g\cdot\alpha_{1}\cdot L_{5}}{2\cdot L_{0}\cdot g}-\frac{m2g\cdot\alpha_{1}\cdot L_{4}}{2\cdot L_{0}\cdot g}=637.9 \text{ N} \quad P_{D}R_{a}=P_{D}+\frac{m1g\cdot\alpha_{1}\cdot L_{5}}{2\cdot L_{0}\cdot g}+\frac{m2g\cdot\alpha_{1}\cdot L_{4}}{2\cdot L_{0}\cdot g}=4262.1 \text{ N}$$

Load applied in lateral direction PntLd

$$P_{At}L_{a} = \frac{m 1 g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = 255.1 \text{ N}$$

$$P_{ct}L_{a} = -\frac{m 1 g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = -255.1 \text{ N}$$

$$P_{bt}L_{a} = -\frac{m 1 g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = -255.1 \text{ N}$$

$$P_{bt}L_{a} = -\frac{m 1 g \cdot \alpha_{1} \cdot L_{3}}{2 \cdot L_{0} \cdot g} = 255.1 \text{ N}$$



5. During deceleration to the right Load applied in radial direction PnRd and Load applied in lateral direction PntRd

$$P_{A}R_{d} = P_{A} - \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot L_{0} \cdot g} - \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 1429.4 \text{ N}$$

$$P_{B}R_{d} = P_{B} + \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot L_{0} \cdot g} + \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 4220.6 \text{ N}$$

$$P_{C}R_{d} = P_{C} + \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot L_{0} \cdot g} + \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 3470.6 \text{ N}$$

$$P_{D}R_{d} = P_{D} - \frac{m1g \cdot \alpha_{3} \cdot L_{5}}{2 \cdot L_{0} \cdot g} - \frac{m2g \cdot \alpha_{3} \cdot L_{4}}{2 \cdot L_{0} \cdot g} = 679.4 \text{ N}$$

Load applied in lateral direction PntRd

$P_{At}R_{d} = -\frac{m_1g \cdot \alpha_3 \cdot L_3}{2 \cdot L_0 \cdot g} = -85 N$	$P_{C_1}R_{d} = \frac{m_1g\cdot\mathcal{A}_3\cdotL_3}{2\cdotL_0\cdotg} = 85N$
$P_{B_1}R_d = \frac{m 1 g \cdot \alpha_3 \cdot L_3}{2 \cdot L_0 \cdot g} = 85 N$	$P_{D_1}R_d = -\frac{m_1g \cdot \alpha_3 \cdot L_3}{2 \cdot L_0 \cdot g} = -85 N$

1.In uniform motion PEn

 $P_{EA} = P_A = 2325 N$

 $P_{EB} = P_{B} = 3325 \text{ N}$

 $P_{ED} = P_{D} = 1575 N$

 $P_{EC} = P_{C} = 2575 N$

2. During acceleration to the left PEnLa PEnLa 3. During deceleration to the left PEnLa $P_{EA}L_a = |P_AL_a| + |P_{At}L_a| = 617 N$ PEALd = PALd + PAtLd = 3305.6 N

 $P_{EB}L_a = |P_BL_a| + |P_{Bt}L_a| = 6267.1 \text{ N}$

 $P_{EC}L_{a} = |P_{C}L_{a}| + |P_{Ct}L_{a}| = 5517.1 \text{ N}$

PEDLa = | PDLa | + | PDtLa | = 1367.1 N

 $P_{EB}R_a = |P_BR_a| + |P_{Bt}R_a| = 893 N$

 $P_{EC}R_a = |P_CR_a| + |P_{Ct}R_a| = 367.2 N$

 $P_{ECL_{d}} = |P_{CL_{d}}| + |P_{CtL_{d}}| = 1764.1 \text{ N}$ $P_{ED}L_{d} = |P_{D}L_{d}| + |P_{Dt}L_{d}| = 2555.6 \text{ N}$

 $P_{EB}L_d = |P_BL_d| + |P_{Bt}L_d| = 2514.4 \text{ N}$

5. During deceleration to the right PEnLa 4. During acceleration to the right PEnRa $P_{EA}R_{a} = |P_{A}R_{a}| + |P_{At}R_{a}| = 5237.2 \text{ N}$ $P_{EA}R_d = |P_AR_d| + |P_{At}R_d| = 1514.4 \text{ N}$ Р_{ЕВ}R_d = Р_ВR_d + Р_{Вt}R_d = 4305.6 N $P_{EC}R_{d} = |P_{C}R_{d}| + |P_{Ct}R_{d}| = 3555.6 \text{ N}$ $P_{ED}R_{a} = |P_{D}R_{a}| + |P_{Dt}R_{a}| = 4517.2 \text{ N}$ $P_{ED}R_{d} = |P_{D}R_{d}| + |P_{Dt}R_{d}| = 764.4 \text{ N}$



(4)Static Safety Factor

As shown above, it is during acceleration of the B Linear Guide to the left when the maximum load is exerted on the Linear Guide. Therefore, the static safety factor (fs) becomes as follows :

$$f_{\rm S} = \frac{C_0}{6267.1} = \frac{88329}{6267.1} = 14.9$$

(5)Mean Load Pmn

LINEAR GUIDE

Unbalanced load at each Linear Guide block will cause during acceleration Uniform motion, and deceleration mean load (Pmn) is a requirement to find out nominal life. First, calculate the move distances (S1, S2, S3) during acceleration, uniform motion, and deceleration of Linear.

$$S_1 = \frac{1}{2} t_1 V = \frac{1}{2} (0.05)(0.5)m = 0.0125m = 12.5mm$$
 $S_3 = \frac{1}{2} t_3 V = (0.15)(0.5)m = 0.0375m = 37.5mm$

S2=t2V=(2.8)(0.5)m=1.4m=1400mm

Nominal Life Ls=S1+S2+S3=1450mm

The mean load on each LM block is as follows :

$$P_{M_{A}} = \sqrt[3]{\frac{1}{2 \cdot L_{s}} \left(P_{EA}^{3} (a \cdot S_{1} + P_{EA}^{3} \cdot S_{2} + P_{EA}^{3} (d \cdot S_{3} + P_{EA}^{3} Ra \cdot S_{1} + P_{EA}^{3} \cdot S_{2} + P_{EA}^{3} Rd \cdot S_{3} \right)} = 2367.3N$$

$$\mathsf{Pm}_{\mathsf{B}} = \sqrt{\frac{1}{2 \cdot \mathsf{Ls}}} \left(\mathsf{P}_{\mathsf{EB}}^{3} \ell a \cdot \mathsf{S}_{1} + \mathsf{P}_{\mathsf{EB}}^{3} \cdot \mathsf{S}_{2} + \mathsf{P}_{\mathsf{EB}}^{3} \ell d \cdot \mathsf{S}_{3} + \mathsf{P}_{\mathsf{EB}}^{3} \mathsf{Ra} \cdot \mathsf{S}_{1} + \mathsf{P}_{\mathsf{EB}}^{3} \cdot \mathsf{S}_{2} + \mathsf{P}_{\mathsf{EB}}^{3} \mathsf{Rd} \cdot \mathsf{S}_{3}} \right) = 3355.9 \mathsf{N}$$

$$P_{m} = \sqrt[3]{\frac{1}{2 \cdot L_{s}} (P_{EC}^{3} (a \cdot S_{1} + P_{EC}^{3} \cdot S_{2} + P_{EC}^{3} (d \cdot S_{3} + P_{EC}^{3} (a \cdot S_{1} + P_{EC}^{3} \cdot S_{2} + P_{EC}^{3} (a \cdot S_{3}))} = 2614N$$

$$P_{m_{D}} = \sqrt[3]{\frac{1}{2 \cdot L_{s}} (P_{ED}^{3} a \cdot S_{1} + P_{ED}^{3} \cdot S_{2} + P_{ED}^{3} d \cdot S_{3} + P_{ED}^{3} Ra \cdot S_{1} + P_{ED}^{3} \cdot S_{2} + P_{ED}^{3} Rd \cdot S_{3})} = 1638.9N$$

$$(L_{A} = \frac{C}{f_{W} \cdot P_{MA}})^{3} \cdot 50 = 115939 \text{ km}$$
 $(L_{C} = \frac{C}{f_{W} \cdot P_{MC}})^{3} \cdot 50 = 86113.86 \text{ km}$
 $(L_{B} = \frac{C}{f_{W} \cdot P_{MB}})^{3} \cdot 50 = 40697 \text{ km}$ $(L_{D} = \frac{C}{f_{W} \cdot P_{MD}})^{3} \cdot 50 = 349407.7 \text{ km}$

%From these calculations, 40697 km (the running distance of Linear Guide No.B) is obtained as the service life of the Linear Guide used in a machine or system under the operating conditions specified above.

In the example above, we assume that we have two loads (W1 and W2). If there is only one load W1, W2 should be re-calculated by being set as zero. The appropriate formula determined by condition of loading.

31



Example(2)

LINEAR GUIDE

(1)Operation Conditions-Vertical Installations

Fig. Table (L type) has combined blocks weigh w1 and w2. Furthermore, the mass w0 is applied during uniform ascent by Distance 1000mm. After the mass is dropped, empty table is removed during uniform descent. The table has total four Linear Guide blocks.

Model number: TRH30FE	
(dynamic-load rating : $C = 47 \text{ KN}$)	$L_0 = 300 \text{ m m}$
(static-load rating : C0 = 88.329 KN)	$L_1 = 80 \text{ mm}$
Gravitational Acceleration : $g = 9.8 (m/s^2)$	$L_2 = 50 \text{ mm}$
Mass : m0g = 2000N	L3 = 280 m m
Weight of Table1 : m1g = 4000N	$L_4 = 150 \text{ m m}$
Weight of Table1 : m2g = 2000N	$L_5 = 250 \text{ m m}$





L3

Fig1.7.4 Operating Condition

(2)Load Exerted on the Linear Guide by the Linear Guide Block

Base on the third condition of Linear Guide is regarding vertical motion to figure out load exerted. [please see page 15. No.3]. Combined influence by mog, m1g, m2g.

1.Load exerted on the Linear Guide in radial direction Pnu by the Linear Guide block.

$P_{AU} = \frac{m1g \cdot L_4}{2 \cdot L_0} + \frac{m2g \cdot L_5}{2 \cdot L} + \frac{m0g \cdot L_3}{2 \cdot L_0} = 2767N$	$Pcu = \frac{m1g \cdot L4}{2 \cdot L0} - \frac{m2g \cdot L5}{2 \cdot L} - \frac{m0g \cdot L3}{2 \cdot L0} = -2767N$
$P_{BU=\text{-}}\frac{m1g\cdotL_4}{2\cdotL_0} - \frac{m2g\cdotL_5}{2\cdotL} - \frac{m0g\cdotL_3}{2\cdotL_0} = -2767N$	$P_{DU} = \frac{m_{1}g \cdot L_{4}}{2 \cdot L_{0}} + \frac{m_{2}g \cdot L_{5}}{2 \cdot L} + \frac{m_{0}g \cdot L_{3}}{2 \cdot L_{0}} = 2767N$

Load exerted on the Linear Guide in lateral direction PnTu by the Linear Guide block.

$PATU = \frac{m1g \cdot L_2}{2 \cdot L_0} + \frac{m2g \cdot L_2}{2 \cdot L} + \frac{m0g \cdot L_1}{2 \cdot L_0} = 767N$	$PcT_{U=-}\frac{m1g\cdotL_2}{2\cdotL_0} - \frac{m2g\cdotL_2}{2\cdotL} - \frac{m0g\cdotL_1}{2\cdotL_0} = -767N$
$P_{B}T_{U}=-\frac{m1g\cdotL_2}{2\cdotL_0}-\frac{m2g\cdotL_2}{2\cdotL}-\frac{m0g\cdotL_1}{2\cdotL_0}=-767N$	$P_DT_U = \frac{m_1g\cdotL_2}{2\cdotL_0} + \frac{m_2g\cdotL_2}{2\cdotL} + \frac{m_0g\cdotL_1}{2\cdotL_0} = 767N$

2.Load exerted on the Linear Guide in radial direction PnD by the Linear Guide block.

$P_{AD} = \frac{m1g \cdot L4}{2 \cdot L0} + \frac{m2g \cdot L5}{2 \cdot L} = 1833.3N$	$P_{CD} = -\frac{m1g \cdot L_4}{2 \cdot L_0} - \frac{m2g \cdot L_5}{2 \cdot L} = -1833.3N$
$P_{BD} = -\frac{m_{1}g \cdot L_{4}}{2 \cdot L_{0}} + \frac{m_{2}g \cdot L_{5}}{2 \cdot L} = -1833.3N$	$P_{DD} = \frac{m_{1}g \cdot L_{4}}{2 \cdot L_{0}} + \frac{m_{2}g \cdot L_{5}}{2 \cdot L} = 1833.3N$

Load exerted on the Linear Guide in lateral direction PnTp by the Linear Guide block

$PATD = \frac{m1g \cdot L_2}{2 \cdot L_0} + \frac{m2g \cdot L_2}{2 \cdot L} + \frac{m0g \cdot L_1}{2 \cdot L_0} = 500N$	$P_{CTD=-} \frac{m1g \cdot L_2}{2 \cdot L_0} - \frac{m2g \cdot L_2}{2 \cdot L} - \frac{m0g \cdot L_1}{2 \cdot L_0} = -500N$
$P_{B}T_{D}=-\frac{m_{1}g\cdotL_{2}}{2\cdotL_{0}}-\frac{m_{2}g\cdotL_{2}}{2\cdotL}-\frac{m_{0}g\cdotL_{1}}{2\cdotL_{0}}=-500N$	$P_DT_D = \frac{m_1g\cdotL_2}{2\cdotL_0} + \frac{m_2g\cdotL_2}{2\cdotL} + \frac{m_0g\cdotL_1}{2\cdotL_0} = 500N$

(3)Combined radial and thrust load PEn

1.During ascent	2.During descent
$P_{EAU} = \left P_{AD} \right + \left P_{A} T_{U} \right = 3534 N$	$P_{EAD} = \left P_{AD} \right + \left P_{A} T_{D} \right = 2333.3 N$
$P_{EBU} = \left P_{BD} \right + \left P_{B} T_{U} \right = 3534 N$	$P_{EBD} = P_{BD} + P_BT_D = 2333.3N$
$P_{ECU} = \left P_{CD} \right + \left P_{C} T_{U} \right = 3534 N$	$P_{ECD} = P_{CD} + P_{C}T_{D} = 2333.3N$
Pedu = Pdd + PdTu = 3534N	Pedd = Pdd + PdTd = 2333.3N

(4)Static Safety Factor

LINEAR GUIDE

The static safety factor (fs) of a machine or system under the operating conditions shown above becomes the following :

$$f_{s} = \frac{C_{0}}{3534N} = \frac{88.329}{3534} = 24.99$$

(5)Mean Load Pmn

$$Pm_{A} = \sqrt[3]{\frac{1}{2 \ell s} (P_{EAU}^{3} \ell_{S} + P_{EAD}^{3} \ell_{S})} = 3051.7 \text{ N} \qquad Pm_{\overline{c}} = \sqrt[3]{\frac{1}{2 \ell s} (P_{ECU}^{3} \ell_{S} + P_{ECD}^{3} \ell_{S})} = 3051.7 \text{ N}$$

$$Pm_{\overline{b}} = \sqrt[3]{\frac{1}{2 \ell s} (P_{EBU}^{3} \ell_{S} + P_{EBD}^{3} \ell_{S})} = 3051.7 \text{ N} \qquad Pm_{\overline{c}} = \sqrt[3]{\frac{1}{2 \ell s} (P_{EDU}^{3} \ell_{S} + P_{EDD}^{3} \ell_{S})} = 3051.7 \text{ N}$$

(6)Nominal life Ln (Assume fw=1.2)

$$L_{A} = \left(\frac{C}{f_{W} \cdot P_{mA}}\right)^{3} \cdot 50 \text{ km} = 105704.7 \text{ km} \qquad L_{C} = \left(\frac{C}{f_{W} \cdot P_{mC}}\right)^{3} \cdot 50 \text{ km} = 105704.7 \text{ km}$$
$$L_{B} = \left(\frac{C}{f_{W} \cdot P_{mB}}\right)^{3} \cdot 50 \text{ km} = 105704.7 \text{ km} \qquad L_{D} = \left(\frac{C}{f_{W} \cdot P_{mD}}\right)^{3} \cdot 50 \text{ km} = 105704.7 \text{ km}$$

1-8 Installation of Linear Guide

1-8-1 Datum representation

Jointed rail should be installed by following the arrow sign and ordinal number which is

marked on the surface of each rail (see Fig1.8.1) :



Fig1.8.1 Datum representation

1-8-2 Recognizing of Master Rail

Linear rails to be applied on the same plane are all marked with the same serial number, and "M" is marked at the end of serial number for indicating the master rail, shown as the figure below. The reference side of carriage is the surface where is ground to a specified accuracy. For normal grade (N), it has no mark "M" on rail which means any one of rails with same serial number could be the master rail.







Fig1.8.4

Combined Use of Rail and Carriage

For combined use, the rail and carriage must have the same serial number. When reinstalling the carriage back to the rail, make sure they have the same serial number and the reference side of carriage should be in accordance with that of rail.

1-8-3 For Butt-joint Rail

Accuracy may deviate at joints when carriages pass the joint simultaneously. Therefore, the joints should be interlaced for avoiding such accuracy problem.





1-8-4 Mounting methods

Linear rail is designed to absorb the load of four dimensions; therefore it can be mounted according to the load and structure of the equipment.

Table 1-8-1



Table 1.8.1



1-8-5 Common Fastening Method of Linear Guide

Table 1.8.2

Fastened by pressing both Linear Guide blocks and rail against their respective reference surfaces.	Fastened by using push screws.	
Fastened by using a hold-down plate.	Fastened by using a tapered gib.1	
Fastened by using screws.	Fastened by using a tapered gib.2	
A Seeting Where the Host Machine is Subjected to Impact and Vibration.		

Unit : N-cm

1-8-6 Mounting the Linear Guide

Mounting Procedures

Machine that Requires Rigidity and High Precision. ****



Fig1.8.5 Mounting the Linear Guide on a Machine Susceptible to Vibration and Impact.

Mounting the Linear Guide Rail

(A)Prior to assembly, always remove all burrs, dents, dust, and the like from the mounting surface of the machine on which the Linear Guide is to be installed. (Fig1.8.6)

CAUTION : The Linear Guide is delivered with an anticorrosive oil applied. Prior to assembly, be sure to remove the oil from the reference surface using a wash oil. If the anticorrosive oil is removed, the surface is likely to rust. The application of a low-viscosity spindle oil or the like is therefore recommended.

(B)Gently place an Linear Guide rail on the base, and temporarily tighten the bolts so that the rail lightly contacts the mounting surface. Hold the line–marked side of the Linear Guide rail against matching the base-side reference surface (Fig1.8.7)
CAUTION : Use clean bolts to fasten the Linear Guide.
When inserting bolts into the Linear Guide rail mounting holes, make sure the threads of the bolt and nut are properly aligned. (Fig1.8.8)



Fig 1.8.6 Checking the Mounting Surface.



Fig1.8.7 Holding an Linear Guide rail against the Reference Surface



Fig1.8.8 Checking Bolt Play

Model No	Tightening Torque		
Model No.	Iron	Casting	Aluminum
M2	58.2	39.2	29.4
M2.3	78.4	53.9	39.2
M2.6	118	78.4	58.8
M3	196	127	98.0
M4	412	274	206
M5	882	588	441
M6	1370	921	686
M8	3040	2010	1470
M10	6760	4510	3330
M12	11800	7840	5880
M14	15700	10500	7840
M16	19600	13100	9800
M20	38200	25500	19100
M22	51900	34800	26000
M24	65700	44100	32800
M30	130000	87200	65200

Table1.8.3 Tightening Torque for Hexagonal-Socket Head Bolts

(C)Tighten the Linear Guide rail set screws in sequence, until they lightly contact the rail-mounting side surface (Fig1.8.9).

(D)Using a torque wrench, tightening the mounting bolts to the specified torque (Fig1.8.10).

CAUTION : The sequence for tightening the Linear Guide – rail mounting bolts should start from the center to the end. Following this sequence enables stable accuracy to be achieved.

(E)Following the same procedures for the remaining Linear Guide rails, complete Linear Guide rail installation.

(F)Drive caps into the bolt holes on the Linear Guide rails so that they are flush with the rail top surface.

Mounting the Linear Guide Block

(A)Gently place a table on the Linear Guide blocks and temporarily tighten the mounting bolts.





Fig1.8.10 Full Tightening of Mounting Bolts



Fig1.8.11

(B)Using set screws, hold the master-rail Linear Guide block against the table referenceside surface, and position the table.

(C)Fully tighten the mounting bolts on both the master and subsidiary sides. This completes Linear Guide block installation.

CAUTION : To ensure uniform fastening of the table, tighten the mounting bolts diagonally, as shown in (Fig1.8.11) in accordance with the numbers.

The method specified above minimizes the time required to ensure the straightness of the Linear Guide-rail. Moreover, there is no need to use the fastening knock pins, thereby greatly reducing the required assembly man-hours.





Fig1.8.12 Mounting the Linear Guide without Set Screws on the Master Linear Guide Rail

Mounting the Master Linear Guide Rail

After temporarily tightening the mounting bolts, use a small device or the like to firmly press the rail to the side, against the reference section. Fully tighten the mounting bolts. Repeat this for each mounting bolt in sequence. (Fig1.8.13)



Fig1.8.13 Mounting the master Linear Guide rail

Mounting the Subsidiary Linear Guide Rail

To ensure parallelism of the subsidiary Linear Guide rail with the master Linear Guide rail properly mounted, the following methods are recommended.

Use a Straight Edge

Position a straight edge between the two rails so that it is parallel with the master-Linear Guide-rail-side reference surface, and confirm parallelism using a dial gauge. Using the straight edge as a reference, confirm subsidiary-rail straightness from one end to the other, tightening the mounting bolts in sequence as you go (Fig1.8.14).



Fig1.8.14 Use a straight edge



LINEAR GUIDE

Move the Table

LINEAR GUID

m

Fasten two Linear Guide blocks on the master side to the]table (or a temporary measurement table). Temporary fasten the subsidiary Linear Guide rail and block to thebase and table. From the dial-gauge stand, have a dial gauge contact the subsidiary-rail Linear Guide block side.Move the table from the rail end and check the parallelism between the block and the subsidiary Linear Guide rail,fastening the bolts in sequence as you go. (Fig1.8.15)

Compare to the Master Linear Guide Rail

Make sure the master Linear Guide rail is properly installed. Temporarily fasten the subsidiary Linear

Guide rail in place.Place a table on the Linear Guide

blocks mounted on themaster rail and on the

temporarily fastened subsidiaryLinear Guide rail.

Fully tighten the mounting bolts on the two Linear

Guide blocks on the subsidiary rail. With the remaining

Linear Guide block on the subsidiary rail temporarily

fastened, correct the position of the subsidiary Linear

Guide rail, fully tightening its mounting bolts insequence

Using a jig as shown in (Fig1.8.17) confirm parallelism

between the master-rail-side reference surface and that

of the subsidiary rail at each mounting hole, and fully





Fig1.8.16 Compare to the master Linear Guide rail



Fig1.8.17

***** Sample Installation of the Linear Guide without a Reference Section for the Master Linear Guide Rail *****



Fig1.8.18 Installation of the Linear Guide without a Reference Section for the Master Linear Guide Rail

Mounting the Master Linear Guide Rail Use a temporary reference surface

Linear Guide-rail straightness from end to end can be achieved with the aid of a surface temporarily set as the reference surface near the Linear Guide-rail mounting surface on the base. For this method, however, two Linear Guide blocks must be fastened together, positioned on top of each other, while attached to a measurement plate, as shown in Fig1.8.19.

Use a straight edge

After temporarily tightening the mounting bolts, use a dial gauge to check the straightness of the Linear Guide-rail-side reference surface from end to end, fully tightening the mounting bolts in sequence as you go, as shown in (Fig1.8.20).

To mount the subsidiary Linear Guide rail, follow the procedures specified in the second paragraph on the previous page.







Fig1.8.20 Use a straight edge

51 **TBI TBIMOTION**

as you go. (Fig1.8.16)

Method Using a Jig

tighten the mounting bolt there.

Shoulder Heights and Chamfers

Improper shoulder heights and chamfers of mounting surfaces will cause deviations in accuracy and rail or block interference with the chamfered part. When recommended shoulder heights and chamfers are used, problems with installation accuracy should be eliminated.





Fig1.8.21

Table 1.8.4 Shoulder Heights and Chamfers

Model No.	Max.chamfers of the rail R1	Max.chamfers of the block R2	Max.chamfers of the rail E1	Max.chamfers of the rail E2	Max.chamfers of the block H1
TR15	0.5	0.5	3	4	3.2
TR20	0.5	0.5	3.5	5	4.6
TR25	1.0	.0 0.9 5		5	5.8
TR30	1.0	1.0 1 5		5	7
TR35	1.0	1	6	6	7.5
TR45	1.0	1	8	8	8.9
TR55	1.5	1.5	10	10	13
TR65	1.5	1.5 1.5		10	14.3

1-9 Friction

The construction of Linear Guide are block, rail and motion system which has rolling elements, such as balls and rollers, placed between two raceways. The rolling motion that rolling elements give rise to reduce the frictional resistance to 1/20 th to 1/40 th of that in a slide guide. Static friction, in particular, is much lower in a linear motion system than in other system, and there is little difference between static and dynamic friction, so that stick-slip does not occur. Therefore, Linear Guide could apply in various precision motion system. Frictional resistance in a linear motion system varies with the type of linear motion system, the magnitude of the preload, the viscosity resistance of the lubricant used the load exerted on the system, and other factors. Table shows Friction of Linear Guide.

Formula of Friction :



F : Friction W : Load

- μ : Friction Coefficient
- f: TR Frictional Resistance



Table 1.9.1Friction Coefficient u of Various
Linear Motion Systems μ

Type of Linear Motion System	Friction Coefficient
Linear Guide	0.002~0.003
Ball Spline	0.002~0.003
Linear Guide Roller	0.0050~0.010
Cross Roller Guide	0.0010~0.0025
Linear Ball Slide	0.0006~0.0012

Fig1.9.1

- Load ratio(P/C)
- P : Load
- C : Basic dymamic rating



1-10 Designing of Rigidity

1-10-1 Determining Radial Clearance and the Magnitude of a Preload

Radial Clearance

The radial clearance of the Linear Guide is the displacement of Linear Guide block caused by the vertical plane when the block is lightly pushed forward or backward at the longitudinal center of the Linear Guide rail secured in place.

The radial clearance is divided into Slight Clearance. (ZF), No Preload (ZO), Clearance Z1 (under a light preload), Z2 (under a medium preload) and Z3 (under a heavy preload). The most appropriate clearance can be selected in accordance with the intended applications. The radial clearances and preload values are standardized for each type of Linear Guide.

The radial clearance of the Linear Guide significantly affects its running precision, loadwithstanding performance, and rigidity. It is therefore particularly important to select the correct clearance for your purpose. In generally, a negative clearance has a favorable effect on service life and precision, if the Linear Guide is subjected to significant vibration and impact due to reciprocal motion.

Preload

The preload is an internal load exerted on rolling elements in the Linear Guide block, for the purposes of increasing the block rigidity and reducing clearances. Clearance symbols for the Liner Guide, ZF, Z0, Z1, Z2 and Z3 represent negative clearances resulting from a preload and are expressed in negative values. All Linear Guide models (excluding the separate type) are shipped with their clearances adjusted to user specifications. Therefore, it is not necessary for users to adjust the preload themselves. We will select the clearances best suited to your operating conditions. Please contact *TBI MOTION*.



Fig1.10.1 Relationship Between Preload and Displacement

Table1.10.1

		Preload	
	ZF~Z0 Slight Clearance, Zero Preload.	Z1 Zero Clearance, Light Preload.	Z2 Zero Clearance, Medium preload.
conditions	The loading direction is fixed; impact and vibration are slight; two axes are installed in parallel.	The location in under an overhang and a moment load. The Linear Guide is used in a one-axis configuration.	The location requires light rigidity and is subjected to vibration and impact.
Operating	Very high percision is not required and the sliding resistance must be as low as possible.	The location requires a light load and high precision.	The application is a heavy- cutting machine tool or the like.
Sample applications	Beam-welding machine. Book-binding machine. automatic packing machine. general-industrial-machine. X-and Y-axes. automatic sash-bar finishing machine. welding machine. arec cutter. tool changer. various kinds of maternal feedeer.	Grinding-machine table feed shaft. automatic painting machine. industrial robot. various kinds of high-speed material feeder. NC drilling machine. general-industrial-machine. Z-axis. printed-cricuit-board drilling machine. electric discharge machine. measuring instrument. precision XY table.	Machining center. NC lathe. grinding-machine grinding -wheel feed shaft. milling machine. vertical-and horizontal- boring machines. tool rest guide. machine-tool Z-axis.

Applied Load and Service Life Considering

Preload

When the Linear Guide is used under a preload (medium),the Linear Guide block receives an internal load. Therefore,the service life should be calculated in consideration of thepreload. For preload considerations, please contact us,specifying the model numbers you have selected.

1-10-2 Rigidity

When the Linear Guide receives a load, the balls, Linear Guide blocks, and rails undergo elastic deformation within a permissible range. The ratio of displacement at this deformation to the load received is known as the rigidity value. The rigidity of the Linear Guide increases as the preload increases. Fig shows the differences among the ordinary clearance Z1 and clearance Z2, Z3. As shown,

in the case of the four-way equal-load type, the effect of preloading remains valid until the load increases to some 2.8 times the preloadapplied.



δ= <u>P</u> μm
δ : Displacement
P : Load
K : Rigidity Value

LINEAR GUIDE

The accuracy of Linear Guide is stipulated for each type with regard to dimensional tolerances for running parallelism, height, and width; height difference among Linear Guide blocks installed on the same plane and differences in the rail-to-block lateral distance among Linear Guide blocks installed on the same rail. For details, see the standards tables for the models in question.

Running parallelism

LINEAR GUIDE

When an Linear Guide block runs on a Linear Guide rail bolted to the reference base, if the Linear Guide block reference surface is not fully parallel to the Linear Guide rail reference surface over the entire length of the rail, the two members have insufficient running parallelism.



Difference in height M among Linear Guide blocks

This refers to the difference between the maximum and minimum height (M) of by any Linear Guide block installed on the same plane.

Fig1.11.1 Running parallelism

Difference in rail-to-block lateral distance W2 among Linear Guide blocks

This refers to the difference between the maximum and minimum rail-to-block lateral distance (W2) of by any Linear Guide block installed on a Linear Guide rail.

Note.1

With two or more sets of Linear Guide installed in parallel on the same plane, the tolerances for the rail-to-block lateral distance (W2) and the differences therein among Linear Guide blocks apply to the master – rail side only.

Note.2

Accuracy measurements indicate mean values of measurements taken at the center or central area of each Linear Guide block.

Note.3

Linear Guide rails are smoothly curved so that when they are installed on a machine they are easily straightened, and pressing them onto the machine reference base enables the design accuracy to be achieved. If installed on a base lacking rigidity, such as an aluminum base, the bend of LinearGuide rails may affect machine precision. In such a case, the straightness should be set in advance.

1-11-2 Averaging Effect

The Linear Guide incorporates precision balls with high sphericity, enabling a constrained structure to be created with no clearance. Moreover, in a multiple-axis configuration with the axes arranged in parallel to one another, the component Linear Guides therein combine to form an entire constrained guideway.

That is the misalignment of the machine base on which the Linear Guides are installed can be averaged and absorbed by the constrained structure, regardless of the misalignment – incomplete straightness levelness, and parallelism due to errors in machining and assembly of the machine base. The extent of the averaging effect varies with the degree of misalignment, i.e., errors in length and other dimensions the magnitude of the Linear Guide preload, and the number of axes constrained shows measurements of the motion accuracy of the table shown (perpendicularity in the lateral direction), which were taken by performing arbitrary misalignment of either of the two rails of the table. The averaging effect illustrated above makes it easier to create a guideway with a high degree of motion accuracy.



1-12 Lubrication

Lubrication

For long-term use of a linear motion system under normal conditions, good lubrication is a must. If lubricant is not used, rolling parts wear quickly, and the service life of the system is shortened considerably.

A lubricant :

LINEAR GUIDE

- (1) Reduces friction on moving parts, thereby preventing seizure and lessening wear.
- (2) Forms an oil film on rolling surfaces, thus decreasing stress that develops on the surfaces and safeguarding the system against rolling fatigue.
- (3) Covers metal surfaces with an oil film, thereby preventing rust.

To tap the full functionality of a linear motion system, it is essential to provide lubrication that best meets the system service conditions.

Note: That linear motion systems, even if sealed, cannot completely eliminate leakage of lubricants no matter how negligible the amount of leakage is at any given time. It is therefore necessary to replenish the lubricant periodically according to the operating conditions for the lubricant in question.

Classification of Lubricants

Primarily grease and sliding surface oil are used as lubricants for linear motion systems.

- In general a lubricant must:
- (1) Form a strong oil film.
- (2) Reduce wear as much as possible.
- (3) Have high wear resistance.
- (4) Have high thermal stability.
- (5) Be noncorrosive.
- (6) Be highly rust-preventive.
- (7) Be free from dust and some moisture.
- (8) Be free from significant fluctuations in consistency against repeated agitation of grease.

Table 1.12.1 Lubricants in General Use

Lubricant	Classification	Item
Grease	Lithium-based grease (JS No.2) Urea-base grease (JS No.2)	* 4FB Grease (TBI MOTION) Albania Grease No.2 (Showa Shell Sekiyu) Daphne Eponex Grease No.2 (Idemitsu Kosan) or equivalent.
Oil	Sliding surface oil or turbine oil ISOVG32~68	Super Multi 32 to 68 (Idemitsu Kosan) Vactra No.2S (Mobile Oil) DT Oil (Mobile Oil) Tonner Oil (Showa Shell Sekiyu) or equivalent

※Feeding Should be performed every 100km of travel under normal usage conditions to prevent incomplete lubrication by exhausted lubrication.

1-13Precautions of Linear Guideway

Handling

(1)Tilting the linear guideway may cause the carriage falling out from the rail by their own weight. (2)Beating or Dropping the linear guideway may cause its function to be damage, even if the

- product looks intact.
- (3)Do not disassemble the carriage, this may cause contamination to enter into the carriage or decrease the installation accuracy.

Lubrication

(1)Please remove the anti-rust oil.

(2)Please do not mix different kinds of lubrication.

(3)Lubrication can be varied, please contact TBI MOTION before use.

Usage

(1)The temperature of the place where linear guideways are used should not exceed 80°c. A higher temperature may damage the plastic end cap, do not exceed 100°c in friction. (2)Using under special conditions, such as constant vibration, high dust or the temperature exceed our suggested ... etc., please TBI MOTION contact .

Storage

When storing the linear guideway, enclose it in a package and store it in a horizontal orientation while avoiding high temperature, low temperature and high humidity.



2. TBI MOTION Linear Guide

2-1 The Characteristics of TBI Linear Guide

In an effort to meet customer's requirement, TBI MOTION offers several different types of guides. Except for TR international standard series, TBI MOTION develops TR series with self lubrication system which is designed for environment with high pollution and miniature TM series for small machines and semiconductor industry.

F	-ig2.1.1	TBI MOTION	Linear g	uide table	with all	series
---	----------	------------	----------	------------	----------	--------

Туре	Height of Assembly Type	Square	Flange Mounting from Above ∖ Mounting from Below
	High-Assembly	TRH-V	TRH-F
TR	Low-Assembly	TRS-V	TRS-F
	Middle-Assembly	TRC-V	-
	-	TM-N	-
ТМ	-	TM-W	-

Fig2.1.2 TBI MOTION Linear Guide - Type & Series

Туре	Accessory	Characteristics	End Cap		
	Standard : Top and Bottom Seal + Wiper				
	U : Inner Seal	Global Type			
	UZ : Inner Seal+Double end Seals		Standard type		
	DD : Bottom Seal+Single-lip end seals				
	UD : Inner Seal+Single-lip end seals	Smooth Movement			
TR	XN : Bottom Seal+Double-lip end seals	Strong dust-proof			
	UN:Top Seal+Bottom Seal+ Double-lip end seals	Environment with			
	ZN:Top Seal+Bottom Seal+ Two Double-lip end seals	high pollution	Reinforcement		
	WW : Bottom Seal+Wool felt+ Double-lip end seals	Self-lubrication/	Туре		
	WU : Top Seal+Bottom Seal+Wool felt+ Double-lip end seals	Strong dust-proof			
	WZ : Top Seal+Bottom Seal+Wool felt+ Two Double-lip end seals	low rating load			
-	-	Standard Miniature type			
ΠM	-	Wide Miniature type	Miniature type		

2-2 TRH/TRS/TRC International standard linear guide

2-2-1 TBI MOTION The Characteristics of TR Series

Smooth Movement

TBI MOTION The circulation system of TBI Linear Guide Block designed to perform smooth movement.



High Stability

TBI MOTION Linear Guide block designed under TBI's exclusive patent can increase depth of material to improve the strength capacity and prevent from deflection as high stability.

High Durability

TBI MOTION The exclusive contact point design promotes high rigidity. Moreover, self-aligning balances load rating in all directions. This design also improves performance in running accuracy and service life of the Linear Guide.

Easy Installation with Interchangeability

TBI MOTION Linear Guide by TBI is easy for installation even without fixture. The design of seal is combinable either for side seal or inner seal to save material.



Fig2.2.1		
Item	Name	Amount
1	Block	1
2	End Cap	2
3	Oil tank	2
4	Wool felt	4
5	End Seal	2
6	Spacer	2
(7)	Double end seal	2
8	Mounting	1
9	Circulation tube	4
(10)	Top+Bottom seal	4

Fig2.2.2

Circulation unit : Block, Rail, End Cap, Steel Balls, Circulation tube.

Lubrication unit : Grease Fitting.

Anti-Dust Unit : Wiper, Top and Bottom Seal, Mounting Hole Cap.

2-2-3 TR-series

(Block types)

TBI MOTION offers flange and square types of flange. The assembly height and category lists as below :

Fig2.2.2





LINEAR GUIDE

2-2-4 TR Model Number for Non-interchangable TR Type

TR series can be classified into interchangeable and non-interchangeable types. The sizes are identical; the only difference between the two types is that the accuracy of noninterchangeable types could reach up to UP grade since TBI MOTION makes the linear guide set under strict international regulation. Interchangeable blocks and rails can be freely exchanged; however, the accuracy could be up to H grade only due to technical issue. It is much more convenient for those customers who do not need linear guides with very high accuracy to have interchangeable blocks and rails.

Non-interchangeable type code :



X : Rail with Special Machining

2-2-5 Model Number for Interchangable TR Type



B : Black Oxidation O : Hard Chrome Plating P : Phosphating N : Nickel Plating D : Raydent K : Tapped-Hole Rail X : Rail with Special Machining

Interchangeable Type of rail :

		Ť	R	20 	40	00	- ^	<u>I</u> - <u>B</u>
Nominal Model (Jode I							
Block Type	R : Standard X : Special							
Model of Size 1	5, 20, 25, 30, 35, 45, 55, 65							
Rail Length	Unit : mm							
Accuracy Grade	N : Normal							
Linear Guide Sp B : Black Oxidat	ecial Machining ion O : Hard Chrome Plating P :	Phosphat	ina N	: Nic	kel P	latin		

D: Raydent K: Tapped-Hole Rail X: Rail with Special Machining

TBIMOTION TBI



2-2-6 TRH-V Series Dimension Table

QXl

푀







	Rating	Load	Static permissible moment of load					Wei	ght
Model No.	C	Co	Mx(kgf-mm)	My(kgf-mm)		Mz(kg	f-mm)	Block	Rail
	1000	2206	Single Block					(Kg)	(Kg/III)
	1206	2206	10,430	14,004	70,960	14,004	70,960	0.13	1.32
TRH15VL	1343	2574	19,175	20,429	95,224	20,429	95,224	0.2	
TRH20VN	2050	3696	37,334	33,268	157,298	33,268	157,298	0.26	
TRH20VL	2125	3891	39,299	36,965	176,924	36,965	176,924	0.29	2.28
TRH20VE	2553	5058	51,089	63,229	284,163	63,229	284,163	0.38	
TRH25VN	2581	4503	52,239	43,407	207,324	43,407	207,324	0.54	
TRH25VL	2875	5254	60,945	59,579	277,678	59,579	277,678	0.55	3.17
TRH25VE	3248	6255	72,554	85,112	391,311	85,112	391,311	0.68	
TRH30VN	3807	6483	90,722	74,970	355,321	74,970	355,321	0.76	
TRH30VL	4098	7203	100,803	93,100	438,966	93,100	438,966	0.85	4.54
TRH30VE	4791	9004	126,003	147,000	677,068	147,000	677,068	1.12	
TRH35VN	5090	8346	142,722	106,070	519,799	106,070	519,799	1.31	
TRH35VL	5502	9328	159,512	133,367	656,509	133,367	656,509	1.52	6.27
TRH35VE	6667	12274	209,885	233,977	1,070,533	233,977	1,070,533	2	
TRH45VL	7572	12808	292,657	220,751	1,030,183	220,751	1,030,183	2.7	10.4
TRH45VE	8852	16010	365,821	348,554	1,598,703	348,554	1,598,703	3.58	10.4
TRH55VL	14703	21613	571,342	411,729	2,019,184	411,729	2,019,184	3.60	16.1
TRH55VE	17349	27377	723,699	670,530	3,148,637	670,530	3,148,637	4.70	10.1
TRH65VL	22526	31486	973,074	695,840	3,594,277	695,840	3,594,277	7.76	22 54
TRH65VE	27895	42731	1,320,601	1,307,568	6,312,759	1,307,568	6,312,759	11.15	22.04

Model No	Asse	mbly	(mm)				Blo	ck(mr	n)					I	Rail((mm)							
	н	W2	Е	W	В	J	L	L1	QX ℓ	T1	Oil Hole	Ν	W1	H1	ØD	h	Ød	F						
TRH15VN	20	0.5	0.5	0.5	0.5	0.5	0.5	0.5	2.2	24	26	26	55.9	39.5	MAYE	0.5		-	15	10	7.5		4 5	60
TRH15VL	20	9.5	3.Z	34	20	20	64.4 4	48	IVI4A0	9.5	M4X0.7	ľ	15	13	1.5	0	4.5	00						
TRH20VN						26	74	54																
TRH20VL	30	12	4.6	44	32	30	79	59	M5X5	6.5	M6X1	14	20	16.5	9.5	8.5	6	60						
TRH20VE						50	98	78																
TRH25VN						25	80	59																
TRH25VL	40 12.	40 12.	40	12.5	5.8	48	35	35	92	71	M6X8	11.5	M6X1	14	23	20	11	9	7	60				
TRH25VE								50	109	88														
TRH30VN		45 16				40	95.3	69.3																
TRH30VL	45		16	7	60	40	40	106	80	M8X10	11	M6X1	14	28	23	14	12	9	80					
TRH30VE						60	131	105																
TRH35VN					0 50	50	108	79																
TRH35VL	55	18	7.5	70		00	122	93	M8X10	15	M6X1	14	34	26	14	12	9	80						
TRH35VE						72	152	123																
TRH45VL	70	20.5	80	86	60	60	140	106	M10X15	20.5	DT1/8	125	15	32	20	17	14	105						
TRH45VE	10	20.5	0.3	00	00	80	174	140	MIOXIS	20.5	111/0	12.0	43	52	20	17	14	103						
TRH55VL	80	23 5	13	100	75	75	163	118	M12X18	21	PT1/8	125	53	44	23	20	16	120						
TRH55VE		20.0	.5	100	, 5	95	201.1	156.1	WI ZATO	21	111/0	12.0	55		20	20	.0	120						
TRH65VL	90	31 5	14	126	76	70	197	147	M16X20	19	PT1/8	125	63	53	26	22	18	150						
TRH65VE	90	90	51.5	14	120	10	120	256.5	206.5	WITO/ZU	13	1 1 1/0	12.0	00	55	20	~~	10	150					



TRH-F Series Dimension Table







Model No.	Asse	embly	(mm)					Bloc	k(mm)					l	Rail((mm)	
would no.	н	W2	Е	W	В	J	t	L	L1	QX ℓ	T1	Oil Hole	Ν	W1	H1	ØD	h	Ød	F
TRH15FN	24	16	32	47	38	30	8	55.9	39.5	M5X8	55	M4X0 7	7	15	13	75	6	45	60
TRH15FL	2.	10	0.2		00	00	0	64.4	48	Moxe	0.0		,	10	10	1.0	Ŭ	1.0	
TRH20FN								74	54										
TRH20FL	30	21.5	4.6	63	53	40	10	79	59	M6X10	6.5	M6X1	14	20	16.5	9.5	8.5	6	60
TRH20FE								98	78										
TRH25FN								80	59										
TRH25FL	36	23.5	5.8	70	57	45	12	92	71	M8X12	7.5	M6X1	14	23	20	11	9	7	60
TRH25FE								109	88										
TRH30FN								95.3	69.3										
TRH30FL	42	31	7	90	72	52	15	106	80	M10X15	8	M6X1	14	28	23	14	12	9	80
TRH30FE								131	105										
TRH35FN								108	79										
TRH35FL	48	33	7.5	100	82	62	15	122	93	M10X15	8	M6X1	14	34	26	14	12	9	80
TRH35FE								152	123										
TRH45FL	60	27 5	80	120	100	80	10	140	106	M12V19	10.5	DT1/9	125	15	32	20	17	14	105
TRH45FE		57.5	0.9	120	100	80	10	174	140	IVIIZAIO	10.5	F11/0	12.5	45	32	20	17	14	105
TRH55FL	70	12 5	10	140	110	05	20	163	118	M1 4V17	11	DT1/0	105	E2	44	22	20	16	120
TRH55FE		43.5	15	140	110	95	29	201.1	156.1	IVI 14A 17		F11/0	12.5	55	44	23	20	10	120
TRH65FL	00	50 F	4.4	170	140	110	27	197	147	MACYOO	10		10 E	62	50	26	22	10	150
TRH65FE	90	53.5	14	170	142	110	37	256.5	206.5	10723	23 19	P11/8	12.5	03	53	20	22	10	150

	Raung	Static permissible moment of load						vve	gnt
Model No.	(k	igt)	Mx(kgf-mm)	My(kg	f-mm)	Mz(kg	ıf-mm)	Block	Rail
	С	Co	Single Block	Single Block	Double Block	Single Block	Double Block	(kg)	(kg/m)
TRH15FN	1206	2206	16,436	14,884	70,960	14,884	70,960	0.18	1.32
TRH15FL	1343	2574	19,175	20,429	95,224	20,429	95,224	0.22	1.02
TRH20FN	2050	3696	37,334	33,268	157,298	33,268	157,298	0.39	
TRH20FL	2125	3891	39,299	36,965	176,924	36,965	176,924	0.43	2.28
TRH20FE	2553	5058	51,089	63,229	284,163	63,229	284,163	0.58	
TRH25FN	2581	4503	52,239	43,407	207,324	43,407	207,324	0.60	
TRH25FL	2875	5254	60,945	59,579	277,678	59,579	277,678	0.67	3.17
TRH25FE	3248	6255	72,554	85,112	391,311	85,112	391,311	0.85	
TRH30FN	3807	6483	90,722	74,970	355,321	74,970	355,321	1.01	
TRH30FL	4098	7203	100,803	93,100	438,966	93,100	438,966	1.18	4.54
TRH30FE	4791	9004	126,003	147,000	677,068	147,000	677,068	1.54	
TRH35FN	5090	8346	142,722	106,070	519,799	106,070	519,799	1.47	
TRH35FL	5502	9328	159,512	133,367	656,509	133,367	656,509	1.72	6.27
TRH35FE	6667	12274	209,885	233,977	1,070,533	233,977	1,070,533	2.29	
TRH45FL	7572	12808	292,657	220,751	1,030,183	220,751	1,030,183	2.80	10.4
TRH45FE	8852	16010	365,821	348,554	1,598,703	348,554	1,598,703	3.79	10.4
TRH55FL	14703	21613	571,342	411,729	2,019,184	411,729	2,019,184	4.22	16.1
TRH55FE	17349	27377	723,699	670,530	3,148,637	670,530	3,148,637	5.6	10.1
TRH65FL	22526	31486	973,074	695,840	3,594,277	695,840	3,594,277	9.31	22 54
TRH65FE	27895	42731	1,320,601	1,307,568	6,312,759	1,307,568	6,312,759	12.98	22.07



TRS-V Series Dimension Table

푀

ļΠ







	Ratin	g Load		Static permi	ssible mome	nt of load		VVe	ight
Model No.	(K	.gr)	Mx(kgf-mm)	My(kg	ıf-mm)	Mz(kg	f-mm)	Block	Rail
	С	Со	Single Block	Single Block	Double Block	Single Block	Double Block	(kg)	(kg/m)
TRS15VS	908	1471	10,957	6,420	33,531	6,420	33,531	0.09	1 2 2
TRS15VN	1206	2206	16,436	14,884	70,960	14,884	70,960	0.15	1.52
TRS20VS	1398	2140	21,615	10,700	59,798	10,700	59,798	0.15	2.28
TRS20VN	1896	3307	33,404	26,459	126,998	26,459	126,998	0.23	2.20
TRS25VS	1943	3002	34,826	18,725	97,890	18,725	97,890	0.25	3 17
TRS25VN	2581	4503	52,239	43,407	207,324	43,407	207,324	0.39	0.17
TRS30VS	2697	3962	55,442	26,950	154,224	26,950	154,224	0.48	
TRS30VN	3807	6483	90,722	74,970	355,321	74,970	355,321	0.77	4.54
TRS30VL	4098	7203	100,803	93,100	438,966	93,100	438,966	0.74	
TRS35VS	3753	5401	92,349	42,896	235,304	42,896	235,304	0.71	
TRS35VN	5090	8346	142,722	106,070	519,799	106,070	519,799	1.15	6.27
TRS35VE	6667	12274	209,885	233,977	1,070,533	233,977	1,070,533	1.54	
TRS45VN	6758	10887	248,758	158,011	782,271	158,011	782,271	1.98	10.4

Medel Nie	Asse	embly	(mm)				Blo	ck(mr	n)					I	Rail((mm)	
wodel No.	н	W2	Е	W	В	J	L	L1	QXℓ	T1	Oil Hole	Ν	W1	H1	ØD	h	Ød	F
TRS15VS	24	0.5	2.2	24	26	\square	39.3	22.9	MAXE		M4X0 7	7	15	12	7 5	6	1 5	60
TRS15VN	24	9.5	3.2	34	20	26	55.9	39.5	101470	5.5	1014/0.7	[′]	15	13	1.5	0	4.5	00
TRS20VS			4.0	40	20		47.8	27.8	MEXE	4.5	MOVA		00	40.5	0.5	0.5	0	
TRS20VN	28	11	4.6	42	32	32	66.7	46.7	101572	4.5	IVIOX1	14	20	16.5	9.5	8.5	6	60
TRS25VS	33	12 5	5.8	48	35		56.2	35.2	Mexe	45	M6X1	14	23	20	11	a	7	60
TRS25VN		12.0	0.0			35	80	59	WIOXO		WOXT	'	20	20			ľ	
TRS30VS							66.4	40.4										
TRS30VN	42	16	7	60	40	40	95.3	69.3	M8X8	8	M6X1	14	28	23	14	12	9	80
TRS30VL						40	106	80										
TRS35VS							74.7	45.7										
TRS35VN	48	18	7.5	70	50	50	108	79	M8X8	8	M6X1	14	34	26	14	12	9	80
TRS35VE						72	152	123										
TRS45VN	60	20.5	8.9	86	60	60	124.5	90.5	M10X15	10.5	PT1/8	12.5	45	32	20	17	14	105



TRS-F Series Dimension Table



Model No.	Asse	mbly	(mm)				Bloo	ck(mn	ר)						l	Rail	(mm	I)	
Woder No.	н	W2	Е	W	В	J	t	L	L1	QXℓ	T1	Oil Hole	Ν	W1	H1	ØD	h	Ød	F
TRS15FS	24	19.5	22	52 41 7 39.3 22.9 M5X7		5 5	MAYO 7	7	15	12	7.5	6	4.5	60					
TRS15FN	24	10.5	3.2	52	41	26	l '	55.9	39.5		5.5	101470.7	<i>'</i>	15	13	1.5		4.5	00
TRS20FS	20	10 E	4.6	50	40	\square	0	47.8	27.8	MCYO	4 5	MOVA	4.4	20	10 5	0.5	0 5	6	60
TRS20FN	20	19.5	4.0	29	49	32	9	66.7	46.7	IVIDA9	4.5		14	20	10.5	9.5	0.0	0	60
TRS25FN	33	25	5.8	73	60	35	10	80	59	M8X10	4.5	M6X1	14	23	20	11	9	7	60



	Rating	Load		Static permis	ssible momer	nt of load		Wei	ght
Model No.	(K	gr)	Mx(kgf-mm)	My(kg	lf-mm)	Mz(kg	lf-mm)	Block	Rail
	С	Co	Single Block	Single Block	Double Block	Single Block	Double Block	(kg)	(kg/m)
TRS15FS	908	1471	10,957	6,420	33,531	6,420	33,531	0.12	1 32
TRS15FN	1206	2206	16,436	14,884	70,960	14,884	70,960	0.19	1.52
TRS20FS	1398	2140	21,615	10,700	59,798	10,700	59,798	0.19	0.00
TRS20FN	1896	3307	33,404	26,459	126,998	26,459	126,998	0.29	2.28
TRS25FN	2581	4503	52,239	43,407	207,324	43,407	207,324	0.51	3.17

TRC-V Series Dimension Table





Model No	Asse	embly	(mm)				Blo	ck(mr	n)					I	Rail((mm)	
MOUELINO.	н	W2	Е	W	В	J	L	L1	QXℓ	T1	Oil Hole	Ν	W1	H1	ØD	h	Ød	F
TRC25VL	36	125	5.8	18	35	35	92	71	M6X6.5	75	M6X1	1/	23	20	11	۵	7	60
TRC25VE	50	12.0	5.0	-0	55	50	109	88	101070.5	1.5	WOAT	14	23	20		3	'	00





	Rating	g Load	S	Static permis	sible momen	t of load		Wei	ight
Model No.	(K	.gr)	Mx(kgf-mm)	My(kg	f-mm)	Mz(kg	f-mm)	Block	"Rạil
	C	Co	Single Block	Single Block	Double Block	Single Block	Double Block	(kg)	(kg/m)
TRC25VL	2875	5254	60,945	59,579	277,678	59,579	277,678	0.52	3 17
TRC25VE	3248	6255	72,554	85,112	391,311	85,112	391,311	0.65	5.17



2-2-7 The Standard length and maxima length of linear rail

TBI MOTION offer our customer standard and customized rail length to meet the requirement for our customer. TBI suggsts that when ordering customized rail length, to prevent unsstablize running performance after mounting, the end cap value G should be no greater than 1/2P.



Fig2.2.3

n: Number of mounting holes

L: Total length of rail (mm)

F: Distance between any two holes (mm)



hole to the edge (mm)

Table2.2.3

 $L=[n-1] \cdot F+2 \cdot G$

Item	TR15	TR20	TR25	TR30	TR35	TR45	TR55	TR65
F: Pitch	60	60	60	80	80	105	120	150
G : Distance to End	20	20	20	20	20	22.5	30	35
L: Max. Length	4000	4000	4000	4000	4000	4000	4000	4000

2-2-8 Type

Besides the standard top mounting type, *TBI MOTION* also offers bottom mounting type rails.

Fig2.2.4





Fig2.2.4 Monting from below

Table2.2.5 Rail Size Chart

Unit : mm

	М	h	E	F
TR15	M5 · 0.8P	8	20	60
TR20	M6 · 1P	10	20	60
TR25	M6 · 1P	12	20	60
TR30	M8 · 1.25P	15	20	80
TR35	M8 · 1.25P	17	20	80
TR45	M12 · 1.75P	24	22.5	105
TR55	M14 · 2P	24	30	120
TR65	M20 · 2.5P	30	35	150



TBI

2-2-9 Accuracy Standard

The accuracy standards of TR-Series range, from normal, high, precision, super-precision and ultra-precision. It allows our user to choose according to the accuracy standards of the equipment.



С





Fig2.10.1 Accuracy Standard

TR Rail Length and Running Accuracy.

Fig2.2.6

Fig2.2.6	ig2.2.6 Unit : mm										
				Accura	cy Stand	ard					
		TR 15	20				TR	25 30) 35		
Accuracy Standard	Normal	High	Precision	Super Precision	Ultra Precision	Normal	High	Precision	Super Precision	Ultra Precision	
Item	N	н	Р	SP	UP	N	н	Р	SP	UP	
Tolerance for height M	±0.1	±0.03	0 -0.03	0 -0.015	0 -0.008	±0.1	±0.04	0 -0.04	0 -0.02	0 -0.01	
Tolerance for height M difference among Linear Guide Block	0.02	0.01	0.006	0.004	0.003	0.02	0.015	0.007	0.005	0.003	
Tolerance for rail-to-block lateral distance W2	±0.1	±0.03	0 -0.03	0 -0.015	0 -0.008	±0.1	±0.04	0 -0.04	0 -0.02	0 -0.01	
Tolerance for rail-to -block lateral distance W2 difference among Linear Guide Block	0.02	0.01	0.006	0.004	0.003	0.03	0.015	0.007	0.005	0.003	
Running parallelism of Linear Guide Block surface C with respect to surface A	riangle C, TR F	Rail Length a	and Running	Fig2.10.1)	riangle C, TR F	Rail Length a	and Running	Accuracy(F	Fig2.10.1)		
Running parallelism of Linear Guide Block surface Dwith respect to surface B	∆ D, TR F	Rail Length a	and Running	Fig2.10.1)	∆ D, TR F	Rail Length a	and Running	g Accuracy(F	Fig2.10.1)		
		TR 45	55					TR 65	5		
Accuracy Standard	Normal	High	Precision	Super Precision	Ultra Precision	Normal	High	Precision	Super Precision	Ultra Precision	
Item	N	Н	Р	SP	UP	N	Н	Р	SP	UP	
Tolerance for height M	±0.1	±0.05	0 -0.05	0 -0.03	0 -0.02	±0.1	±0.07	0 -0.07	0 -0.05	0 -0.03	
Tolerance for height M difference among Linear Guide Block	0.03	0.015	0.007	0.005	0.003	0.03	0.02	0.01	0.007	0.005	
Tolerance for rail-to-block lateral distance W2	±0.1	±0.05	0 -0.05	0 -0.03	0 -0.02	±0.1	±0.07	0 -0.07	0 -0.05	0 -0.03	
Tolerance for rail-to -block lateral distance W2 difference among Lnear Guide Block	0.03	0.02	0.01	0.007	0.005	0.03	0.025	0.015	0.01	0.007	
Running parallelism of Linear Guide Block surface C with respect to surface A	∆ C, TR F	Rail Length a	and Running	g Accuracy(I	Fig2.10.1)	∆ C, TR F	Rail Length a	and Running	g Accuracy(F	Fig2.10.1)	
Running parallelism of Linear Guide Block surface Dwith respect to surface B	∆ D, TR F	Rail Length a	and Running	g Accuracy(I	Fig2.10.1)	∆ D, TR F	Rail Length a	and Running	g Accuracy(F	Fig2.10.1)	



2-2-10 Determining the Magnitude of a Preload

What's Preload

Replacing larger rolling elements helps strengthen the entire rigidity of the carriage while there exists clearance with in ball circulation.

Increasing preload would decrease the vibration and reduce the corrosion caused by running back and forth. However, it would also add the workload within those rolling elements. The greater the preload, the greater the inner workload. Therefore, choosing preload has to consider the effect carefully between vibration and preload.

Table2.2.7 Grade of Pre	load	C : Dynamic load rating
Grade	Symbol	Preload force
Slight Clearance	ZF	0
No Preload	Z0	0
Light Preload	Z1	0.02C
Medium Preload	Z2	0.05C
Heavy Preload	Z3	0.07C

Table2.2.8 TR Series Radial Clearances

Unit : μ m

Preload Model No.	ZF	Z0	Z1	Z2	Z3
TR15	5~12	-4~4	-12~-5	-20~-13	-28~-21
TR20	6~14	-5~5	-14~-6	-23~-15	-32~-24
TR25	7~16	-6~6	-16~-7	-26~-17	-36~-27
TR30	8~18	-7~7	-18~-8	-29~-19	-40~-30
TR35	9~20	-8~8	-20~-9	-32~-21	-44~-33
TR45	10~22	-9~9	-22~-10	-35~-23	-48~-36
TR55	11~24	-10~10	-24~-11	-38~-25	-52~-39
TR65	12~26	-11~11	-26~-12	-41~-27	-56~-42

Table2.2.9 The difference between Interchageability and Non-Interchageability

		Non-Ir	Intercha	ngeable			
Slight Clearance	UP	SP	Р	Н	N	Н	N
					ΖF		ZF
			Z 0	Z 0	Z 0	Z 0	Z0
Preload	Z 1	Z 1	Z 1	Z 1	Z 1	Z 1	Z 1
	Z2	Z 2	Ζ2	Z 2	Ζ2		
	Ζ3	Z 3	Z 3	Z 3			

2-2-11 Grease Nipples

Table2.2.10 Grease Nipples



Mounting Location

The standard location of the grease fitting is at both ends of the block, but the nipple can be mounted at each side of block. For lateral installation, we recommend that the nipple be mounted at the non-reference side, otherwise please contact us. It is possible to perform lubrication by using the oil-piping joint.



Fig2.2.7 Mounting Location

	The lubricant amount
	IOI a DIOCK IIIEU WILLI
Table2.2.11	grease

Size	Grease(cm ³)
TR15	1.3
TR20	2.5
TR25	2.5
TR30	7
TR35	9
TR45	15.2
TR55	40
TR65	75

Table2.2.12 Oil refilling rate

Size	Oil refilling rate (cm ² /hr)
TR15	0.2
TR20	0.2
TR25	0.3
TR30	0.3
TR35	0.3
TR45	0.4
TR55	0.5
TR65	0.6

Table 2.2.13 Type of Lubrication Coupler

SD-037

TR15





2-2-12 Dust-proof / Linear Guide Self-lubrication Series Accessory

TBI MOTION Linear Guide with Strong Dust-proof End Seal

Characteristics of TBI MOTION Dust-proof End Seal

- 1. Seal Function: Seal design from single-lip to double-lips to prevent more dust go into the block.
- Hardness: Heat treatment for end seals to make hardness higher in order to absorb high impact when operation.
- 3. Environment: Better solution for dust-proof when using double seals in environment with high pollution.
- 4. Lifetime Extension: Double-lip seal prevents dust go into the block and provides a solution for block damage due to dust issue.

TBI MOTION Linear Guide Self-lubrication Series

There is a wool felt accessory between end cap and seals. Wool felt with oil will lubricate the rail when operating; grease nipple is not needed. The design is shown as below.



Characteristics:

- 1. Easy Assembly and Removal-- Only screws are needed when assemble and disassemble the accessory.
- 2. Environmentally Friendly-- No need of grease nipple and other equipment to save energy.
- 3. Low Maintenance-- Optimized oil usage prevents leaking, making it the ideal solution for clean working environments. Self-lubricating block is maintenance free in most applications.
- $\label{eq:constraint} \text{4.Strong Dust-proof-- With dust-proof accessory, lifetime will be extended.}$

Table2.2.14 Test

	Control Group	Experiment Group
Test Environment	Standard	Self-lubricating
Dimension	TRH20VL	TRH20VL
Rating Load	1000 kg	1000 kg
Speed	6 m/min	6 m/min
Travel Length	600 mm	600 mm





No more grease is added during the test for both standard series and self-lubricating series. Lifetime Comparison As shown in the chart, the lifetime of self-lubricating blocks is one time longer than that of standard series blocks.

Instructions of Self-lubricating Block

It is suggested to soak the wool felt in the oil tank for more than 8 hours before using. The wool felt can be refilled with any approved lubrication oil depending on the requirement (ISOVG 32 ~ 68).

Characteristics of Suggested Oil:

- (1) Form a strong oil film.
- (2) Reduce wear as much as possible.
- (3) Have high wear resistance.
- (4) Have high thermal stability.
- (5) Be noncorrosive.
- (6) Be highly rust-preventive.
- (7) Be free from dust and some moisture.



Codes of accessories

LINEAR GUIDE

If the following accessories are needed, please add the code followed by the model number. Special Option : Steel end seal, Steel end cap, Cover Strip ,contact *TBI MOTION*.

Table2.2.15 Codes of accessories



Table2.2.15 Codes of accessories



WO(Double-lip end seals+Bottom seals+Top Seals+Wool lefts



WZ(Two Double-lip end seals+Bottom seals+Top Seals+Wool felts)



End seal and Bottom seal

To prevent life reduction caused by iron chips or dust entering the block.

Inner Seal

Efficiently avoid dust from the surface of rail or tapping hole getting inside the block.

Double end seal

Enhances the wiping effect, foreign matter can be completely wiped off.

Double-lip end seals

Double-lip end seal is suitable for environment with high pollution.

Wool felt

Double-lip end seal is suitable for environment with high pollution. Wool felt lubricates the ball track of the rail to increase the lifetime. This accessory is suitable for light rating load environment.

Table2.2.16

Spacer	Thickness(mm)
TR15	4
TR20	4.5
TR25	4.5
TR30	4.5
TR35	5
TR45	6
TR55	6
TR65	8



TBIMOTION

TBI

Table2.2.17 TR Type block length of accessories

Unit : mm

							01	iit · mini
	Double-lip end seals(XN \ UN)							
Type Length of Block Code	TR15	TR20	TR25	TR30	TR35	TR45	TR55	TR65
S	40.5	49.4	57.2	67.4	75.7			
Ν	57.1	TRS(68.3) TRH(75.6)	81	96.2	109.2	124.5		
L	65.6	80.6	93	107	123	140	150.4	185.5
E	80.6	99.6	110	132	153	174	188.4	245

Two Double-lip end seals(ZN)								
Type ength of Block Code	TR15	TR20	TR25	TR30	TR35	TR45	TR55	TR65
S	48.1	58.4	65.6	76.4	84.7			
Ν	64.7	TRS(77.3) TRH(84.6)	89.4	105.2	118.2	134.5		
L	73.2	89.6	101.4	116	132	150	161.6	196.5
E	88.2	108.6	118.4	141	162	184	199.6	256

	Double-lip end seals+Wool felt(WW \ WU)							
Type Length of Block Code	TR15	TR20	TR25	TR30	TR35	TR45	TR55	TR65
S	52	69.9	68.7	78.9	87.2			
N	68.6	TRS(79.8) TRH(87.1)	92.5	107.7	120.7	136		
L	77.1	92.1	104.5	118.5	134.5	151.5	161.9	197
E	92.1	111.1	121.5	143.5	164.5	185.5	199.9	256.5

	Two Double-lip end seals+Wool felt(WZ)							
Type Length of Block Code	TR15	TR20	TR25	TR30	TR35	TR45	TR55	TR65
S	59.6	69.9	77.1	87.9	96.2			
Ν	76.2	TRS(88.8) TRH(96.1)	100.9	116.7	129.7	146		
L	84.7	101.1	112.9	127.5	143.5	161.5	173.1	208
E	99.7	120.1	129.9	152.5	173.5	195.5	211.1	267.5

Dustproof Rails

Once the Linear Guide in the cutting machine is in operating, dust and foreign matter that enter the Linear Guide may cause abnormal wear and shorten the service life.

Linear Guide rail mounting-hole cap :

Chips and foreign matter clogging the mounting holes of a Linear Guide rail may enter the Linear Guide block. To prevent from this situation, the mounting holes must be closed with dedicated caps, which must be installed to flush with the Linear Guide rail top surface. To insert a dedicated cap into a mounting hole, drive the cap in using a plastic hammer with a flat metal pad placed on the cap until it is flush with the Linear Guide rail top surface.





Fig2.2.11 Dustproof Rails

Rail with tapped holes :

Fixing a rail with tapped hole is different from fixing a standard one. A major strength of it is the shape of the tapped hole; dust and chippings would not enter.

2-2-13 Friction

The figure showed in the chart is the maximum friction.

Unit : kg					
Model No.	End Cap friction rate(Max)				
TR15	0.25				
TR20	0.35				
TR25	0.4				
TR30	0.5				
TR35	0.7				
TR45	1.3				
TR55	1.6				
TR65	2				

Table 2 2 18 End Cap friction rate



2-2-14 Mounting-Surface Dimensional Tolerance

TR series Linear Guide has a Four-Way Equal-Load design, a slight dimensional error in the mounting surface can be absorbed by the natural self-adjusting capability of the product, thus ensuring smoothy linear motion. In the table below are the dimensional tolerances for the mounting surface of TR Linear Guide.





Unit : µm

Table2.2.19

Model No	Tole	erance fo T\	r Parallel vo Axis(e	ism Betw 1)	een	Tolerance for Parallelism Between Two Axis(e2)					
Model No.	Z3	Z2	Z1	Z0	ZF	Z3	Z2	Z1	Z0	ZF	
TR15			18	25	35			85	130	190	
TR20		18	20	25	35		50	85	130	190	
TR25	15	20	22	30	42	60	70	85	130	195	
TR30	20	27	30	40	55	80	90	110	170	250	
TR35	22	30	35	50	68	100	120	150	210	290	
TR45	25	35	40	60	85	110	140	170	250	350	
TR55	34	45	50	70	98	130	170	210	300	410	
TR65	42	55	60	80	105	150	200	250	350	460	

2-3 TM Miniature Linear Guide

2-3-1 The Characteristics of TM Series

Dust-proof design

The stainless bottom seal is the innovative new design of TBI Motion TM series. It prevents effectively the abnormal chips getting into the ball track from the bottom side of the block and keep the good running performance and extend the life time of the slider because the friction is low by keeping some small backlash between the slider and rail.

Standard end seals provide extreme protection from dust, metal scrapers to maintain long service life and lower maintenance period. Unique low friction seal lips provide best smoothness and lower friction.



Fig2.3.1

High tensile performance stainless steel reinforcement plate

Dual fully covered stainless steel plates design delivers the best coverage for plastic on each ends. Stainless steel screws are used to strength the rigidity, protection with end cap in order to sustain higher operational speed Vmax=5m/s, a max=300m/s², When linear block is equipped with reinforcement plates and dust-proof seal, it can also function as scraper.



Fig2.3.4

Fig2.3.5

High loading and moment capacity performance TM Miniature Linear Guide series uses two row re-circulating methods with Gothic 45' contact angle on the rail groove to achieve equal load capacity in four directions. Larger steel balls are used to enhance the loading and torsion resistance performance in limited space.

Fig2.3.6 The Gothic 45 degrees fourdirection load structure



TBI

TBIMOTION





2-3-3 Accuracy

TM Miniature Linear Guide provides P × H × N three accuracy grades for customer to choose.

Table2.3.1

Accuracy (μ m)		Precision P	High H	Normal
Tolerance of Height H	Н	±10	±20	±40
Variation of height with different block on same spot of the rail	$\triangle H$	7	15	25
Tolerance of width W ₂	W_2	±15	±25	±40
Variation with width on different block on same spot of the rail	$ riangle W_2$	10	20	30

Preload

The maximum acceleration of TM-N can reach Vmax > 5m/s, a max=300 m/s (60/ms before preload).

Table2.3.2 Running parallel precision slide relative to the rails datum



2-3-4 Preload

Preload

TM Miniature Linear Guide offers three preloading level which are ZF, Z0, Z1. A proper preloading will enhance performance on stiffness, precision, and torsion resistance; however an improper preloading will lower service life and increase friction.

Table2.3.3 Table

Preload	Prossuro		Preloa	d(Applications
grade	Flessure	7	9	12	15	Applications
ZF	Zero Preload	+4~0	+4~0	+5~0	+6~0	Running smoothly
Z0	Slight Clearance	+2~0	+2~0	+2~0	+3~0	Precision applications, Running smoothly
Z1	Light Preload	0~-3	0~-4	0~-5	0~-6	High steel, Precision applications, Running smoothly

Permissible Operational Temperature

The TM Miniature Linear Guide is sufficient to operate between $-40^{\circ}C \sim + 80^{\circ}C$. For sudden temperature rise the temperature can reach up to $+100^{\circ}C$.



2-3-5 Types of lubrication

Grease

When a linear guide is well lubricated, the contact point between rail and rolling steel balls will be separated by 1 micro meter. Therefore, a good lubrication increases the life of linear guide.

Clean room lubrication

Suitable for low dust environment.

Lubrication

General usage, ISO V32~68.

Special Oil needs by TBI MOTION

2-3-6 Order Information

Customized Requirement :



Table 2.3.5

Table 2.3.4

Model

TM07NN

TM07NL

TM09NN

TM09NL

TM012NN

TM012NL

TM015NN

TM015NL

Lubrication amount (cc)

0.3

0.4

0.4

0.6

0.9

1.3

1.4

2.0

	SIZE									
Rail Length	TM7	TM9	TM12	TM15						
Pitch(mm)	15	20	25	40						
L2, L3 min	3	4	4	4						
L2, L3 max	10	20	20	35						
Lmax	1300	1300	1300	1300						

2-3-7 Model Number

Lubrication amount (cc)

0.4

0.6

0.9

1.3

1.4

2.0

Model

TM09WN

TM09WL

TM012WN

TM012WL

TM015WN

TM015WL

Junior Mantes

Length of Block

Perform joint treatment when required lengths exceed 1300. Please contact TBI MOTION for detailed information.

	〒 º º º ♥ └ A · 2 · - · <u>1000</u> · N A · Z · - 프 · B
Nominal Model Code	т
Block Type	M : Miniature X : Special (Drawing will be provided for special item in order to distinguish the height of the rail.)
Model of Size	07, 09, 12, 15
Width of Rail	N : Standard W : Wide
Length of Block	N : Standard L : Long
Material	S : Stainless steel A : Alloy steel
Quantity of Block	(Mark 1 when there is only 1 runner block)
Seals Type	□ : Standard (End seal + Side seal)
Rail Length	Unit : mm
Accuracy Grade	N : Normal H : High P : Precision SP : Super-Precision UP : Ultra-Precision
Material	S : Stainless steel A : Alloy steel
Preload	ZF : Slight Clearance Z0 : No Preload Z1 : Light Preload
Two Sets per Axis	(No need to be marked when there is only one rail) Π

Linear Guide Special Machining B: Black Oxidation O: Hard Chrome Plating P: Phosphating N: Nickel Plating D: Raydent K: Tapped-Hole Rail X: Rail with Special Machining



Т





Model No	As	ssemt	oly	Block(mm)								Rail(mm)					
Woder No.	Н	W2	Е	W	В	J	Т	L	L1	Qxℓ	Ø	W1	H1	ØD	h	Ød	F
TM07NN	8	5	1.5	17	12	8	2.25	23	12.3	M2x2	1.3	7	4.7	4.2	2.3	2.4	15
TM07NL	8	5	1.5	17	12	13	2.25	31	20.3	M2x2	1.3	7	4.7	4.2	2.3	2.4	15
TM09NN	10	5.5	2.2	20	15	10	3.62	30.5	19.8	M3x3	1.3	9	5.5	6	3.3	3.5	20
TM09NL	10	5.5	2.2	20	15	16	3.62	40.8	30.1	M3x3	1.3	9	5.5	6	3.3	3.5	20
TM12NN	13	7.5	3	27	20	15	4.54	35	20.6	M3x3.5	1.3	12	7.5	6	4.5	3.5	25
TM12NL	13	7.5	3	27	20	20	4.54	47.5	33.1	M3x3.5	1.3	12	7.5	6	4.5	3.5	25
TM15NN	16	8.5	4	32	25	20	5.86	43	27	M3x5	1.3	15	9.5	6	4.5	3.5	40
TM15NL	16	8.5	4	32	25	25	5.86	60	44	M3x5	1.3	15	9.5	6	4.5	3.5	40

TM-W Specification





Model No	oly	Block(mm)							Rail(mm)									
Model No.	н	W2	Е	W	В	J	Т	L	L1	Qxℓ	Ø	W1	H1	ØD	h	Ød	F	Р
TM09WN	12	6	3.4	30	23	12	4	39.1	26.7	M3x3	1.3	18	7.3	6	4.5	3.5	30	\square
TM09WL	12	6	3.4	30	23	24	4	50.7	38.3	M3x3	1.3	18	7.3	6	4.5	3.5	30	\checkmark
TM12WN	14	8	3.9	40	28	15	4.5	44.4	29	M3x3.5	1.3	24	8.5	8	4.5	4.5	40	\checkmark
TM12WL	14	8	3.9	40	28	28	4.5	59.4	44	M3x3.5	1.3	24	8.5	8	4.5	4.5	40	\checkmark
TM15WN	16	9	4.1	60	45	20	4.8	55.3	38.5	M4x4.5	1.3	42	9.5	8	4.5	4.5	40	23
TM15WL	16	9	4.1	60	45	35	4.8	74.4	57.6	M4x4.5	1.3	42	9.5	8	4.5	4.5	40	23





	Rating	Load		Static permissible moment of load								
Model No.	(K	gi) T	Mx(kgf-mm)	My(kg	ıf-mm)	Mz(kg	f-mm)	Block	Rail			
	С	Co	Single Block	Single Block	Double Block	Single Block	Double Block	(kg)	(kg/m)			
TM07NN	144	204	745	232	3,234	232	3,234	0.005	0.21			
TM07NL	220	374	1,367	849	7,261	849	7,261	0.009	0.21			
TM09NN	220	374	1,713	849	7,117	849	7,117	0.013	0.32			
TM09NL	299	579	2,648	2,099	14,174	2,099	14,174	0.020	0.52			
TM12NN	381	536	3,269	1,094	12,391	1,094	12,391	0.024	0.61			
TM12NL	555	919	5,604	3,437	26,857	3,437	26,857	0.039	0.01			
TM15NN	581	834	6,336	2,316	23,096	2,316	23,096	0.048	1			
TM15NL	860	1,459	11,088	7,527	52,908	7,527	52,908	0.080				

Мx



	Rating	Load		Static permissible moment of load							
Model No.	(К		Mx(kgf-mm)	My(kg	ıf-mm)	Mz(kg	f-mm)	Block	Rail		
	С	Co	Single Block	Single Block	Double Block	Single Block	Double Block	(kg)	(kg/m)		
TM09WN	208	368	4,645	1,621	12,205	1,621	12,205	0.03	0.07		
TM09WL	260	509	7,123	3,905	23,411	3,905	23,411	0.043	0.97		
TM12WN	313	530	10,190	2,864	23,153	2,864	23,153	0.05	1 47		
TM12WL	415	796	15,748	7,083	46,164	7,083	46,164	0.076	1.47		
TM15WN	517	856	26,387	5,459	42,543	5,459	42,543	0.116	2.85		
TM15WL	686	1,283	41,779	14,144	87,256	14,144	87,256	0.175	2.00		

TBI MOTION Linear Guideway Inquiry Form

Customer :	Date :
TEL :	Email : Confirm By :
Machine Type :	Drawing No.
Axis :	□ X □ Y □ Z □ Other ()
Install Position	
Model No.	
No. of Rail Per Axis	□1 □2 □3 □4 □Other:
Dust Protection	Standard U UZ UD XN UN ZN WW WU WZ Other
Rail Length / Butt-joint	□Length mm Butt-joint : □NO □YES
Pitch	G1: G2:
Accessory Code	$\square N(\text{Normal}) \ \square H(\text{High}) \ \square P(\text{Precision}) \ \square SP(\text{Super Precision}) \ \square UP(\text{Ultra Precision})$
Preload	ZF(Slight Clearance) ZO(No Preload) Z1(Light Preload) Z2(Medium Preload) Z3(Heavy Preload)
Rail Per Axis	□1 □2 □3 □Others :
Rail Mounting	□ From Top □K From Bottom □X Rail with Special Maching
Special Cladding	$\square B(\text{Black Oxidation}) \ \ \square \ O(\text{Hard Chrome Plating}) \ \ \square \ P(\text{Phosphating}) \ \ \square \ N(\text{Nickel Plating}) \ \ \square \ D(\text{Raydent})$
Lubrication Type	□Grease □Oil
Lubrication Fitting	□Grease nipple (Code:) □Oil piping joint (Code:)
Special Option	□Steel end seal □Steel end cap □Cover Strip □Other :
TBI MOTION Model No.	
Reference surface & Injection Direction	

MEMO